



T3 POWER PLUS COMPACTOR

The THETFORD T3 POWER PLUS compactor is available with 40 psi ram face pressure, 46 second cycle time as standard or with up to 80 psi ram face pressure with twin cylinders and cycle time of 23 to 92 seconds. Twin or Single cylinder models can be supplied with any type of hopper or chute, side/rear loader attachments, internal or external power pack, left or right hand loading and controls, or to suit any specific requirements.

THIS DOCUMENT IS NOT TO BE COPIED, REPRODUCED OR DISCLOSED TO A THIRD PARTY WITHOUT THE WRITTEN CONSENT OF THETFORD. THETFORD RESERVE THE RIGHT TO CHANGE SPECIFICATION WITHOUT PRIOR NOTICE.



Rymer Point, Bury Road, Thetford, Norfolk IP24 2PN

Tel: (01842) 890500

Fax: (01842) 890077

E-mail: sales-serv@thetford-int.co.uk

Web: www.thetford-int.co.uk

T3 POWER PLUS COMPACTOR

Metric

Charge Box Volume	1.67m ³
Hopper Volume	3.46m ³
CHEM Rating per Volume Stroke	1.43m ³
Volume per Hour (CHEM)	112m ³
Charge Box Length	1.549m
Charge Box Width	1.511m
Ram Depth	0.61m
Ram Width	1.505m
Cycle Time	46 secs
Running Thrust	23,151 kg
Pinning Thrust	26,136 kg
Running Pressure	179 bar
Pinning Pressure	202 bar
Ram Face Pressure	2.76 bar
Electric Motor	7.5kw
Mains Supply Fuses	32 amp
Control Fuses	25 amp

Shipping Dimensions

Compactor Overall Length	3.874m
Compactor Overall Width	1.93m
Compactor Main Frame Height	1.168m
Deck Height	1.270m
Nominal Mainframe Weight	3450kg

THIS DOCUMENT IS NOT TO BE COPIED, REPRODUCED OR DISCLOSED TO A THIRD PARTY WITHOUT THE WRITTEN CONSENT OF THETFORD. THETFORD RESERVE THE RIGHT TO CHANGE SPECIFICATION WITHOUT PRIOR NOTICE.