

USER INSTRUCTIONS

TECHNICAL DATA

Model		VEC01	VEC02	VEC03	VEC04
Item	Datasheet	1P+N+PE	3P+N+PE	1P+N+PE	3P+N+PE
Input	Power Supply	AC220 ~ 240V 50/60Hz	AC380 ~ 415V 50/60Hz	AC220 ~ 240V 50/60Hz	AC380 ~ 415V 50/60Hz
	Rated Voltage	Max 32A (6-32A adjustable)			
	Rated current	AC220 ~ 240V 50/60Hz	AC380 ~ 415V 50/60Hz	AC220 ~ 240V 50/60Hz	AC380 ~ 415V 50/60Hz
Output	Output Voltage	AC220 ~ 240V 50/60Hz	AC380 ~ 415V 50/60Hz	AC220 ~ 240V 50/60Hz	AC380 ~ 415V 50/60Hz
	Maximum Current	Max 32A (6-32A adjustable)			
	Rated Power	7.4KW	22KW	7.4KW	22KW
Configuration	Charger socket or connector	Type 2			
	Material	ABS +PC Flammability Rating V - 0			
	Colour	Black			
	Indicator light	Three colour LED			
Safety	Ingress Protection	IP54			
	PCB protection	Over current protection The max 32A-Recommended 36A			
		Residual current protection (AC Type A 30mA, DC6mA)			
		Earth check			
		Over/Under voltage protection			
		Over temperature protection			
		PEN fault protection			
	Certification	CE, UKCA			
Power consumption	Standby power consumption	<10W			
	Installation	Wall mounted			
Enviroment	Work Temperature	-25°C~50°C			
	Work Humidity	3%~95%			
	Work Altitude	<2000m			