



Technical Key Account Manager

Reference – PLA - LRH

PPG Architectural Coatings UK Limited
Huddersfield Road, Birstall, Batley, West
Yorkshire, WF17 9XA,
www.ppgpmc.com

Martin Hayday

Dear Brad,

Please find below specification proposal for the sheet pile refurbishments.

System description: Epoxy system for maintenance, suitable for ISO 12944-2:1998, Im3 High

Preparation: Coated Steel; hydrojetted to min. VIS WJ2L leaving steel with a blasting profile 30-75µm / 1.2-3mils.

PDS	Product name	Colour	DFT (µm)	TSR (L/m2)	Thinner Description
7743	Sigmashield 880	BLACK	250	0.85	Thinner 91-92
7743	Sigmashield 880	BLACK	250	0.85	Thinner 91-92

Notes:

1. Note that areas of breakdown of clutch sealant not repaired may be a weak point in coating system.
2. Product can be applied a single sprayed coat or multiple coats by brush and roller to achieve required film build.

This coatings system is designed to meet ISO 12944-2 IM2, high durability. Should you require test lab report of performance to meet this standard, or details of the track record for Sigmashield 880 please do not hesitate to contact me.

Best Regards,

Martin Hayday
PPG Protective Coatings UK & Ireland
T: 07342 079522
E: hayday@ppg.com

