

RCD		Page 1																																																																																																																																										
9 Birchtree Way Maidstone Kent ME15 7RP	THE BUILDERS YARD LOWER RANGE ROAD GRAVESEND																																																																																																																																											
Date 23/08/2022 12:33 File 1190-2202-B.MDX	Designed by RAC Checked by																																																																																																																																											
Micro Drainage Network 2020.1.3																																																																																																																																												
STORM SEWER DESIGN by the Modified Rational Method Design Criteria for Storm Pipe Sizes STANDARD Manhole Sizes STANDARD FSR Rainfall Model - England and Wales <table><tr><td>Return Period (years)</td><td>1</td><td>PIMP (%)</td><td>100</td></tr><tr><td>M5-60 (mm)</td><td>26.250</td><td>Add Flow / Climate Change (%)</td><td>0</td></tr><tr><td>Ratio R</td><td>0.350</td><td>Minimum Backdrop Height (m)</td><td>0.000</td></tr><tr><td>Maximum Rainfall (mm/hr)</td><td>0</td><td>Maximum Backdrop Height (m)</td><td>10.000</td></tr><tr><td>Maximum Time of Concentration (mins)</td><td>30</td><td>Min Design Depth for Optimisation (m)</td><td>1.200</td></tr><tr><td>Foul Sewage (l/s/ha)</td><td>0.000</td><td>Min Vel for Auto Design only (m/s)</td><td>1.00</td></tr><tr><td>Volumetric Runoff Coeff.</td><td>0.750</td><td>Min Slope for Optimisation (1:X)</td><td>500</td></tr></table> Designed with Level Soffits Time Area Diagram for Storm <table><tr><td>Time (mins)</td><td>Area (ha)</td><td>Time (mins)</td><td>Area (ha)</td></tr><tr><td>0-4</td><td>0.071</td><td>4-8</td><td>0.013</td></tr></table> Total Area Contributing (ha) = 0.084 Total Pipe Volume (m³) = 6.432			Return Period (years)	1	PIMP (%)	100	M5-60 (mm)	26.250	Add Flow / Climate Change (%)	0	Ratio R	0.350	Minimum Backdrop Height (m)	0.000	Maximum Rainfall (mm/hr)	0	Maximum Backdrop Height (m)	10.000	Maximum Time of Concentration (mins)	30	Min Design Depth for Optimisation (m)	1.200	Foul Sewage (l/s/ha)	0.000	Min Vel for Auto Design only (m/s)	1.00	Volumetric Runoff Coeff.	0.750	Min Slope for Optimisation (1:X)	500	Time (mins)	Area (ha)	Time (mins)	Area (ha)	0-4	0.071	4-8	0.013																																																																																																						
Return Period (years)	1	PIMP (%)	100																																																																																																																																									
M5-60 (mm)	26.250	Add Flow / Climate Change (%)	0																																																																																																																																									
Ratio R	0.350	Minimum Backdrop Height (m)	0.000																																																																																																																																									
Maximum Rainfall (mm/hr)	0	Maximum Backdrop Height (m)	10.000																																																																																																																																									
Maximum Time of Concentration (mins)	30	Min Design Depth for Optimisation (m)	1.200																																																																																																																																									
Foul Sewage (l/s/ha)	0.000	Min Vel for Auto Design only (m/s)	1.00																																																																																																																																									
Volumetric Runoff Coeff.	0.750	Min Slope for Optimisation (1:X)	500																																																																																																																																									
Time (mins)	Area (ha)	Time (mins)	Area (ha)																																																																																																																																									
0-4	0.071	4-8	0.013																																																																																																																																									
Network Design Table for Storm <table><tr><th>PN</th><th>Length (m)</th><th>Fall (m)</th><th>Slope (1:X)</th><th>I.Area (ha)</th><th>T.E. (mins)</th><th>Base Flow (l/s)</th><th>k (mm)</th><th>HYD SECT</th><th>DIA (mm)</th><th>Section Type</th><th>Auto Design</th></tr><tr><td>1.000</td><td>31.000</td><td>0.150</td><td>206.7</td><td>0.020</td><td>5.00</td><td>0.0</td><td>0.600</td><td>o</td><td>300</td><td>Pipe/Conduit</td><td></td></tr><tr><td>1.001</td><td>15.000</td><td>0.100</td><td>150.0</td><td>0.000</td><td>0.00</td><td>0.0</td><td>0.600</td><td>o</td><td>300</td><td>Pipe/Conduit</td><td></td></tr><tr><td>2.000</td><td>21.000</td><td>0.100</td><td>210.0</td><td>0.010</td><td>5.00</td><td>0.0</td><td>0.600</td><td>o</td><td>300</td><td>Pipe/Conduit</td><td></td></tr><tr><td>2.001</td><td>11.000</td><td>0.050</td><td>220.0</td><td>0.005</td><td>0.00</td><td>0.0</td><td>0.600</td><td>o</td><td>300</td><td>Pipe/Conduit</td><td></td></tr><tr><td>2.002</td><td>7.000</td><td>0.050</td><td>140.0</td><td>0.049</td><td>0.00</td><td>0.0</td><td>0.600</td><td>o</td><td>300</td><td>Pipe/Conduit</td><td></td></tr></table> Network Results Table <table><tr><th>PN</th><th>Rain (mm/hr)</th><th>T.C. (mins)</th><th>US/IL E (m)</th><th>Σ I.Area (ha)</th><th>Σ Base Flow (l/s)</th><th>Foul (l/s)</th><th>Add Flow (l/s)</th><th>Vel (m/s)</th><th>Cap (l/s)</th><th>Flow (l/s)</th></tr><tr><td>1.000</td><td>0.00</td><td>5.47</td><td>3.200</td><td>0.020</td><td>0.0</td><td>0.0</td><td>0.0</td><td>1.09</td><td>77.0</td><td>0.0</td></tr><tr><td>1.001</td><td>0.00</td><td>5.67</td><td>3.050</td><td>0.020</td><td>0.0</td><td>0.0</td><td>0.0</td><td>1.28</td><td>90.6</td><td>0.0</td></tr><tr><td>2.000</td><td>0.00</td><td>5.32</td><td>3.250</td><td>0.010</td><td>0.0</td><td>0.0</td><td>0.0</td><td>1.08</td><td>76.4</td><td>0.0</td></tr><tr><td>2.001</td><td>0.00</td><td>5.50</td><td>3.150</td><td>0.015</td><td>0.0</td><td>0.0</td><td>0.0</td><td>1.06</td><td>74.6</td><td>0.0</td></tr><tr><td>2.002</td><td>0.00</td><td>5.59</td><td>3.100</td><td>0.064</td><td>0.0</td><td>0.0</td><td>0.0</td><td>1.33</td><td>93.8</td><td>0.0</td></tr></table>			PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design	1.000	31.000	0.150	206.7	0.020	5.00	0.0	0.600	o	300	Pipe/Conduit		1.001	15.000	0.100	150.0	0.000	0.00	0.0	0.600	o	300	Pipe/Conduit		2.000	21.000	0.100	210.0	0.010	5.00	0.0	0.600	o	300	Pipe/Conduit		2.001	11.000	0.050	220.0	0.005	0.00	0.0	0.600	o	300	Pipe/Conduit		2.002	7.000	0.050	140.0	0.049	0.00	0.0	0.600	o	300	Pipe/Conduit		PN	Rain (mm/hr)	T.C. (mins)	US/IL E (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)	1.000	0.00	5.47	3.200	0.020	0.0	0.0	0.0	1.09	77.0	0.0	1.001	0.00	5.67	3.050	0.020	0.0	0.0	0.0	1.28	90.6	0.0	2.000	0.00	5.32	3.250	0.010	0.0	0.0	0.0	1.08	76.4	0.0	2.001	0.00	5.50	3.150	0.015	0.0	0.0	0.0	1.06	74.6	0.0	2.002	0.00	5.59	3.100	0.064	0.0	0.0	0.0	1.33	93.8	0.0
PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design																																																																																																																																	
1.000	31.000	0.150	206.7	0.020	5.00	0.0	0.600	o	300	Pipe/Conduit																																																																																																																																		
1.001	15.000	0.100	150.0	0.000	0.00	0.0	0.600	o	300	Pipe/Conduit																																																																																																																																		
2.000	21.000	0.100	210.0	0.010	5.00	0.0	0.600	o	300	Pipe/Conduit																																																																																																																																		
2.001	11.000	0.050	220.0	0.005	0.00	0.0	0.600	o	300	Pipe/Conduit																																																																																																																																		
2.002	7.000	0.050	140.0	0.049	0.00	0.0	0.600	o	300	Pipe/Conduit																																																																																																																																		
PN	Rain (mm/hr)	T.C. (mins)	US/IL E (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)																																																																																																																																		
1.000	0.00	5.47	3.200	0.020	0.0	0.0	0.0	1.09	77.0	0.0																																																																																																																																		
1.001	0.00	5.67	3.050	0.020	0.0	0.0	0.0	1.28	90.6	0.0																																																																																																																																		
2.000	0.00	5.32	3.250	0.010	0.0	0.0	0.0	1.08	76.4	0.0																																																																																																																																		
2.001	0.00	5.50	3.150	0.015	0.0	0.0	0.0	1.06	74.6	0.0																																																																																																																																		
2.002	0.00	5.59	3.100	0.064	0.0	0.0	0.0	1.33	93.8	0.0																																																																																																																																		
©1982-2020 Innovyze																																																																																																																																												

RCD										Page 2																																																		
9 Birchtree Way Maidstone Kent ME15 7RP					THE BUILDERS YARD LOWER RANGE ROAD GRAVESEND																																																							
Date 23/08/2022 12:33 File 1190-2202-B.MDX					Designed by RAC Checked by																																																							
Micro Drainage					Network 2020.1.3																																																							
<u>Network Design Table for Storm</u> <table><tr><th>PN</th><th>Length (m)</th><th>Fall (m)</th><th>Slope (1:X)</th><th>I.Area (ha)</th><th>T.E. (mins)</th><th>Base Flow (l/s)</th><th>k (mm)</th><th>HYD SECT</th><th>DIA (mm)</th><th>Section</th><th>Type</th><th>Auto Design</th></tr><tr><td>1.002</td><td>6.000</td><td>0.050</td><td>120.0</td><td>0.000</td><td>0.00</td><td>0.0</td><td>0.600</td><td>o</td><td>300</td><td>Pipe/Conduit</td><td></td><td></td></tr></table> <u>Network Results Table</u> <table><tr><th>PN</th><th>Rain (mm/hr)</th><th>T.C. (mins)</th><th>US/IL (m)</th><th>Σ I.Area (ha)</th><th>Σ Base Flow (l/s)</th><th>Foul (l/s)</th><th>Add Flow (l/s)</th><th>Vel (m/s)</th><th>Cap (l/s)</th><th>Flow (l/s)</th></tr><tr><td>1.002</td><td>0.00</td><td>5.74</td><td>2.950</td><td>0.084</td><td>0.0</td><td>0.0</td><td>0.0</td><td>1.43</td><td>101.4</td><td>0.0</td></tr></table>													PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section	Type	Auto Design	1.002	6.000	0.050	120.0	0.000	0.00	0.0	0.600	o	300	Pipe/Conduit			PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)	1.002	0.00	5.74	2.950	0.084	0.0	0.0	0.0	1.43	101.4	0.0
PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section	Type	Auto Design																																																
1.002	6.000	0.050	120.0	0.000	0.00	0.0	0.600	o	300	Pipe/Conduit																																																		
PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)																																																		
1.002	0.00	5.74	2.950	0.084	0.0	0.0	0.0	1.43	101.4	0.0																																																		
©1982-2020 Innovyze																																																												

RCD

9 Birchtree Way
Maidstone
Kent ME15 7RP

THE BUILDERS YARD
LOWER RANGE ROAD
GRAVESEND

Date 23/08/2022 12:33
File 1190-2202-B.MDX

Designed by RAC
Checked by

Micro Drainage

Network 2020.1.3

Manhole Schedules for Storm

MH Name	MH CL (m)	MH Depth (m)	MH Connection	MH Diam., L*W (mm)	Pipe Out PN Invert Level (m)	Diameter (mm)	Pipes In PN Invert Level (m)	Diameter (mm)	Backdrop (mm)
1	4.000	0.800	Open Manhole	600	1.000	3.200	300		
2	4.000	0.950	Open Manhole	600	1.001	3.050	300	1.000	3.050
re	4.000	0.750	Open Manhole	600	2.000	3.250	300		
3	4.000	0.850	Open Manhole	600	2.001	3.150	300	2.000	3.150
4	4.000	0.900	Open Manhole	600	2.002	3.100	300	2.001	3.100
5	4.000	1.050	Open Manhole	1200	1.002	2.950	300	1.001	2.950
								2.002	3.050
ex	4.000	1.100	Open Manhole	1200		OUTFALL		1.002	2.900

No coordinates have been specified, layout information cannot be produced.

Gravesham Borough Council

©1982-2020 Innovyze

RCD		Page 4
9 Birchtree Way Maidstone Kent ME15 7RP		THE BUILDERS YARD LOWER RANGE ROAD GRAVESEND
Date 23/08/2022 12:33 File 1190-2202-B.MDX		Designed by RAC Checked by
Micro Drainage		Network 2020.1.3



PIPELINE SCHEDULES for Storm

Upstream Manhole

PN	Hyd Sect	Diam (mm)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
1.000	o	300	1	4.000	3.200	0.500	Open Manhole	600
1.001	o	300	2	4.000	3.050	0.650	Open Manhole	600
2.000	o	300	re	4.000	3.250	0.450	Open Manhole	600
2.001	o	300	3	4.000	3.150	0.550	Open Manhole	600
2.002	o	300	4	4.000	3.100	0.600	Open Manhole	600
1.002	o	300	5	4.000	2.950	0.750	Open Manhole	1200

Downstream Manhole

PN	Length (m)	Slope (1:X)	MH Name	C.Level (m)	I.Level (m)	D.Depth (m)	MH Connection	MH DIAM., L*W (mm)
1.000	31.000	206.7	2	4.000	3.050	0.650	Open Manhole	600
1.001	15.000	150.0	5	4.000	2.950	0.750	Open Manhole	1200
2.000	21.000	210.0	3	4.000	3.150	0.550	Open Manhole	600
2.001	11.000	220.0	4	4.000	3.100	0.600	Open Manhole	600
2.002	7.000	140.0	5	4.000	3.050	0.650	Open Manhole	1200
1.002	6.000	120.0	ex	4.000	2.900	0.800	Open Manhole	1200

Free Flowing Outfall Details for Storm

Outfall Pipe Number	Outfall Name	C. Level (m)	I. Level (m)	Min I. Level (m)	D,L (mm)	W (mm)
1.002	ex	4.000	2.900	2.900	1200	0

Simulation Criteria for Storm

Volumetric Runoff Coeff	0.750	Additional Flow - % of Total Flow	0.000
Areal Reduction Factor	1.000	MADD Factor * 10m³/ha	Storage 2.000
Hot Start (mins)	0	Inlet Coefficient	0.800
Hot Start Level (mm)	0	Flow per Person per Day (l/per/day)	0.000
Manhole Headloss Coeff (Global)	0.500	Run Time (mins)	60
Foul Sewage per hectare (l/s)	0.000	Output Interval (mins)	1
Number of Input Hydrographs	0	Number of Storage Structures	1
Number of Online Controls	1	Number of Time/Area Diagrams	0
Number of Offline Controls	0	Number of Real Time Controls	0

Synthetic Rainfall Details

©1982-2020 Innovyze

RCD		Page 5																				
9 Birchtree Way Maidstone Kent ME15 7RP	THE BUILDERS YARD LOWER RANGE ROAD GRAVESEND																					
Date 23/08/2022 12:33 File 1190-2202-B.MDX	Designed by RAC Checked by																					
Micro Drainage Network 2020.1.3																						
<u>Synthetic Rainfall Details</u> <table> <tr> <td>Rainfall Model</td> <td>FSR</td> <td>Profile Type</td> <td>Summer</td> </tr> <tr> <td>Return Period (years)</td> <td>1</td> <td>Cv (Summer)</td> <td>0.750</td> </tr> <tr> <td>Region</td> <td>England and Wales</td> <td>Cv (Winter)</td> <td>0.840</td> </tr> <tr> <td>M5-60 (mm)</td> <td>26.250</td> <td>Storm Duration (mins)</td> <td>30</td> </tr> <tr> <td>Ratio R</td> <td>0.350</td> <td></td> <td></td> </tr> </table>			Rainfall Model	FSR	Profile Type	Summer	Return Period (years)	1	Cv (Summer)	0.750	Region	England and Wales	Cv (Winter)	0.840	M5-60 (mm)	26.250	Storm Duration (mins)	30	Ratio R	0.350		
Rainfall Model	FSR	Profile Type	Summer																			
Return Period (years)	1	Cv (Summer)	0.750																			
Region	England and Wales	Cv (Winter)	0.840																			
M5-60 (mm)	26.250	Storm Duration (mins)	30																			
Ratio R	0.350																					
©1982-2020 Innovyze																						

RCD		Page 6
9 Birchtree Way Maidstone Kent ME15 7RP	THE BUILDERS YARD LOWER RANGE ROAD GRAVESEND	
Date 23/08/2022 12:33 File 1190-2202-B.MDX	Designed by RAC Checked by	
Micro Drainage Network 2020.1.3		
<u>Online Controls for Storm</u> <u>Orifice Manhole: 5, DS/PN: 1.002, Volume (m³): 2.6</u> Diameter (m) 0.025 Discharge Coefficient 0.600 Invert Level (m) 2.950		
©1982-2020 Innovyze		

RCD		Page 7																																																																																																																								
9 Birchtree Way Maidstone Kent ME15 7RP	THE BUILDERS YARD LOWER RANGE ROAD GRAVESEND																																																																																																																									
Date 23/08/2022 12:33 File 1190-2202-B.MDX	Designed by RAC Checked by																																																																																																																									
Micro Drainage Network 2020.1.3																																																																																																																										
<u>Storage Structures for Storm</u> <u>Porous Car Park Manhole: 4, DS/PN: 2.002</u> <table><tr><td>Infiltration Coefficient Base (m/hr)</td><td>0.00000</td><td>Width (m)</td><td>10.0</td></tr><tr><td>Membrane Percolation (mm/hr)</td><td>1000</td><td>Length (m)</td><td>44.0</td></tr><tr><td>Max Percolation (l/s)</td><td>122.2</td><td>Slope (1:X)</td><td>0.0</td></tr><tr><td>Safety Factor</td><td>2.0</td><td>Depression Storage (mm)</td><td>5</td></tr><tr><td>Porosity</td><td>0.30</td><td>Evaporation (mm/day)</td><td>3</td></tr><tr><td>Invert Level (m)</td><td>3.550</td><td>Membrane Depth (mm)</td><td>0</td></tr></table> <u>Volume Summary (Static)</u> Length Calculations based on Centre-Centre <table><thead><tr><th>Pipe Number</th><th>USMH Name</th><th>Manhole Volume (m³)</th><th>Pipe Volume (m³)</th><th>Storage Structure Volume (m³)</th><th>Total Volume (m³)</th></tr></thead><tbody><tr><td>1.000</td><td>1</td><td>0.226</td><td>2.191</td><td>0.000</td><td>2.417</td></tr><tr><td>1.001</td><td>2</td><td>0.269</td><td>1.060</td><td>0.000</td><td>1.329</td></tr><tr><td>2.000</td><td>re</td><td>0.212</td><td>1.484</td><td>0.000</td><td>1.696</td></tr><tr><td>2.001</td><td>3</td><td>0.240</td><td>0.778</td><td>0.000</td><td>1.018</td></tr><tr><td>2.002</td><td>4</td><td>0.254</td><td>0.495</td><td>59.400</td><td>60.149</td></tr><tr><td>1.002</td><td>5</td><td>1.188</td><td>0.424</td><td>0.000</td><td>1.612</td></tr><tr><td>Total</td><td></td><td>2.389</td><td>6.432</td><td>59.400</td><td>68.222</td></tr></tbody></table> <u>Volume Summary (Static)</u> Length Calculations based on True Length <table><thead><tr><th>Pipe Number</th><th>USMH Name</th><th>Manhole Volume (m³)</th><th>Pipe Volume (m³)</th><th>Storage Structure Volume (m³)</th><th>Total Volume (m³)</th></tr></thead><tbody><tr><td>1.000</td><td>1</td><td>0.226</td><td>2.149</td><td>0.000</td><td>2.375</td></tr><tr><td>1.001</td><td>2</td><td>0.269</td><td>0.997</td><td>0.000</td><td>1.265</td></tr><tr><td>2.000</td><td>re</td><td>0.212</td><td>1.442</td><td>0.000</td><td>1.654</td></tr><tr><td>2.001</td><td>3</td><td>0.240</td><td>0.735</td><td>0.000</td><td>0.975</td></tr><tr><td>2.002</td><td>4</td><td>0.254</td><td>0.431</td><td>59.400</td><td>60.086</td></tr><tr><td>1.002</td><td>5</td><td>1.188</td><td>0.339</td><td>0.000</td><td>1.527</td></tr><tr><td>Total</td><td></td><td>2.389</td><td>6.093</td><td>59.400</td><td>67.882</td></tr></tbody></table>			Infiltration Coefficient Base (m/hr)	0.00000	Width (m)	10.0	Membrane Percolation (mm/hr)	1000	Length (m)	44.0	Max Percolation (l/s)	122.2	Slope (1:X)	0.0	Safety Factor	2.0	Depression Storage (mm)	5	Porosity	0.30	Evaporation (mm/day)	3	Invert Level (m)	3.550	Membrane Depth (mm)	0	Pipe Number	USMH Name	Manhole Volume (m³)	Pipe Volume (m³)	Storage Structure Volume (m³)	Total Volume (m³)	1.000	1	0.226	2.191	0.000	2.417	1.001	2	0.269	1.060	0.000	1.329	2.000	re	0.212	1.484	0.000	1.696	2.001	3	0.240	0.778	0.000	1.018	2.002	4	0.254	0.495	59.400	60.149	1.002	5	1.188	0.424	0.000	1.612	Total		2.389	6.432	59.400	68.222	Pipe Number	USMH Name	Manhole Volume (m³)	Pipe Volume (m³)	Storage Structure Volume (m³)	Total Volume (m³)	1.000	1	0.226	2.149	0.000	2.375	1.001	2	0.269	0.997	0.000	1.265	2.000	re	0.212	1.442	0.000	1.654	2.001	3	0.240	0.735	0.000	0.975	2.002	4	0.254	0.431	59.400	60.086	1.002	5	1.188	0.339	0.000	1.527	Total		2.389	6.093	59.400	67.882
Infiltration Coefficient Base (m/hr)	0.00000	Width (m)	10.0																																																																																																																							
Membrane Percolation (mm/hr)	1000	Length (m)	44.0																																																																																																																							
Max Percolation (l/s)	122.2	Slope (1:X)	0.0																																																																																																																							
Safety Factor	2.0	Depression Storage (mm)	5																																																																																																																							
Porosity	0.30	Evaporation (mm/day)	3																																																																																																																							
Invert Level (m)	3.550	Membrane Depth (mm)	0																																																																																																																							
Pipe Number	USMH Name	Manhole Volume (m³)	Pipe Volume (m³)	Storage Structure Volume (m³)	Total Volume (m³)																																																																																																																					
1.000	1	0.226	2.191	0.000	2.417																																																																																																																					
1.001	2	0.269	1.060	0.000	1.329																																																																																																																					
2.000	re	0.212	1.484	0.000	1.696																																																																																																																					
2.001	3	0.240	0.778	0.000	1.018																																																																																																																					
2.002	4	0.254	0.495	59.400	60.149																																																																																																																					
1.002	5	1.188	0.424	0.000	1.612																																																																																																																					
Total		2.389	6.432	59.400	68.222																																																																																																																					
Pipe Number	USMH Name	Manhole Volume (m³)	Pipe Volume (m³)	Storage Structure Volume (m³)	Total Volume (m³)																																																																																																																					
1.000	1	0.226	2.149	0.000	2.375																																																																																																																					
1.001	2	0.269	0.997	0.000	1.265																																																																																																																					
2.000	re	0.212	1.442	0.000	1.654																																																																																																																					
2.001	3	0.240	0.735	0.000	0.975																																																																																																																					
2.002	4	0.254	0.431	59.400	60.086																																																																																																																					
1.002	5	1.188	0.339	0.000	1.527																																																																																																																					
Total		2.389	6.093	59.400	67.882																																																																																																																					
©1982-2020 Innovyze																																																																																																																										

RCD

9 Birchtree Way
Maidstone
Kent ME15 7RP

THE BUILDERS YARD
LOWER RANGE ROAD
GRAVESEND

Date 23/08/2022 12:33
File 1190-2202-B.MDX

Designed by RAC
Checked by

Micro Drainage

Network 2020.1.3

Page 8



100 year Return Period Summary of Critical Results by Maximum Level (Rank 1) for Storm

Simulation Criteria

Areal Reduction Factor 1.000

Additional Flow - % of Total Flow 0.000

Hot Start (mins) 0

MADD Factor * 10m³/ha Storage 2.000

Hot Start Level (mm) 0

Inlet Coefficient 0.800

Manhole Headloss Coeff (Global) 0.500

Flow per Person per Day (l/per/day) 0.000

Foul Sewage per hectare (l/s) 0.000

Number of Input Hydrographs 0

Number of Storage Structures 1

Number of Online Controls 1

Number of Time/Area Diagrams 0

Number of Offline Controls 0

Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model

FSR

Ratio R 0.350

Region England and Wales Cv (Summer) 0.750

M5-60 (mm)

26.250 Cv (Winter) 0.840

Margin for Flood Risk Warning (mm)

300.0

Analysis Timestep 2.5 Second Increment (Extended)

DTS Status

ON

DVD Status

ON

Inertia Status

ON

Profile(s)

Summer and Winter

Duration(s) (mins)

15, 30, 60, 120, 180, 240, 360, 480, 600, 720, 960, 1440, 2160, 2880, 4320, 5760, 7200, 8640, 10080

Return Period(s) (years)

100

Climate Change (%)

40

PN	US/MH Name	Storm	Return Period	Climate Change	First (X) Surge	First (Y) Flood	First (Z) Overflow	Overflow Act.	Water Level (m)
1.000	1	360 Winter	100	+40%	100/15 Summer				3.925
1.001	2	360 Winter	100	+40%	100/15 Summer				3.924
2.000	re	360 Winter	100	+40%	100/15 Summer				3.921
2.001	3	360 Winter	100	+40%	100/15 Summer				3.921
2.002	4	360 Winter	100	+40%	100/15 Summer				3.921
1.002	5	360 Winter	100	+40%	100/15 Summer				3.924

Surcharged Flooded					Half Drain	Pipe			
PN	US/MH Name	Depth (m)	Volume (m³)	Flow / Cap.	Overflow (l/s)	Time (mins)	Flow (l/s)	Status	Level Exceeded
1.000	1	0.425	0.000	0.03			2.2	FLOOD RISK	
1.001	2	0.574	0.000	0.03			2.2	FLOOD RISK	
2.000	re	0.371	0.000	0.02			1.1	FLOOD RISK	
2.001	3	0.471	0.000	0.03			1.6	FLOOD RISK	

©1982-2020 Innovyze

RCD		Page 9
9 Birchtree Way Maidstone Kent ME15 7RP	THE BUILDERS YARD LOWER RANGE ROAD GRAVESEND	
Date 23/08/2022 12:33 File 1190-2202-B.MDX	Designed by RAC Checked by	
Micro Drainage		Network 2020.1.3

100 year Return Period Summary of Critical Results by Maximum Level (Rank 1) for Storm

PN	US/MH Name	Surcharged	Flooded	Flow / Cap.	Overflow (l/s)	Half Drain	Pipe	Status	Level Exceeded
		Depth (m)	Volume (m³)			Time (mins)	Flow (l/s)		
2.002	4	0.521	0.000	0.02		369	1.4	FLOOD RISK	
1.002	5	0.674	0.000	0.02			1.3	FLOOD RISK	

©1982-2020 Innovyze