



Woodward

frogged brick in two distinct finishes - smooth and antique

HEIGHT



65

Millimetres

FINISHES

Sm

Smooth

Ant

Antique

215 x 65 x
102.5mm

COLOURS

For 'Stock Information' on colours and finish availability - see page 3.



ASHBROOKE SMOOTH




ASHBROOKE ANTIQUE




CLARENDON BLUE SMOOTH




CLARENDON BLUE ANTIQUE




HAMPTON SMOOTH



HAMPTON ANTIQUE



TULLAMORE SMOOTH





TULLAMORE ANTIQUE



EDENMORE SMOOTH



EDENMORE ANTIQUE

LYNDHURST SMOOTH **new**LYNDHURST ANTIQUE **new**SHANDON SMOOTH **new**SHANDON ANTIQUE **new**DURROW CREAM SMOOTH **new**DURROW CREAM ANTIQUE **new**OLDTOWN MULTI SMOOTH **new**OLDTOWN MULTI ANTIQUE **new**LEWIS SMOOTH **new**LEWIS ANTIQUE **new**

Frost
Resistant



Very Low
Risk of
Efflorescence



Very Low
Water
Absorption



Specials
Available



Woodward

frogged brick in two distinct finishes - smooth and antique

HEIGHT


65

Millimetres

FINISHES

Sm

Smooth

Ant

Antique

 215 x 65 x
 102.5mm

COLOURS

For 'Stock Information' on colours and finish availability - see page 3.



VINTAGE WHITE SMOOTH **new**




VINTAGE WHITE ANTIQUE **new**



OLDE DUBLIN BUFF SMOOTH
new



OLDE DUBLIN BUFF ANTIQUE
new




WICKLOW SMOOTH **new**



WICKLOW ANTIQUE **new**



DOONMORE SMOOTH **new**



DOONMORE ANTIQUE **new**



Frost
Resistant



Very Low
Risk of
Efflorescence



Very Low
Water
Absorption



Specials
Available



Woodward

frogged brick in two distinct finishes - smooth and antique

HEIGHT


65

Millimetres

FINISHES

Sm

Smooth

Ant

Antique

 215 x 65 x
102.5mm

SUSTAINABILITY

Energy Use	100% renewable
Water Used	100% rain water harvesting
Recyclable	100% of this product can be recycled
Manufacturing	Produced in the UK using responsibly sourced materials
Waste Wood + Plastic:	100% recycled

BREEAM 'A+' Rating – in accordance with the BRE Green Guide to Specification.

Information for a specific colour is available on request from our Technical Specification Department.

ADVICE + GUIDANCE

For advice and guidance on ordering, installation, good site practice, etc. visit our website:
www.ag.uk.com/advice+guidance

For maintenance guidance and health and safety advice visit our website:
www.ag.uk.com/maintenance

FEATURES + BENEFITS

- Available in two finishes - a smooth finish with crisp edges for a contemporary look; and an antique finish with rumbled edges for a more traditional look.
- Woodward bricks are frogged, so they are lighter and easier to handle than solid bricks.
- The frog creates an extra recess for the mortar, resulting in a stronger bond between bricks.
- Frogged bricks reduce the environmental impact as the indentation in the brick saves on materials, which also helps reduce the curing time of the bricks.

AG RECOMMENDATIONS

Frog

Woodward bricks should be laid with the frog facing upwards and completely filled with mortar.

Colour blending


Products should be mixed on site from a minimum of 3 packs to help reduce the effect of banding.

Mortar Ratio


Recommended ratio 6 : 1 or 5 : 1 (Sand : OPC).

EDGES

Woodward Brick is supplied with either crisp, clean edges (smooth finish) or distressed, round edges (antique finish).



Smooth



Antique

FINISHES

Woodward Brick comes in two finishes.

Smooth for a contemporary feel and a chic, modern look.

Antique with the rumbled, distressed finish of old reclaimed brick and all of the benefits of new brick.


 Frost
Resistant

 Very Low
Risk of
Efflorescence

 Very Low
Water
Absorption

 Specials
Available

MANUFACTURING

Woodward concrete facing bricks are manufactured by using advanced manufacturing processes and natural materials. All products are manufactured from natural materials and although we strive to provide consistency of colour, variation may occur in the manufacturing process - this applies to all concrete products within the industry. PLANT OF MANUFACTURE: Made at our Fivemiletown Production Plant.

CERTIFICATION

ISO 9001
ISO 14001
ISO 45001
CE Marking

Quality Management.
Environmental Management.
Occupational Health and Safety Management.
Download our Declaration of Performance (DOP) data at: www.ag.uk.com/resources



Woodward

froged brick in two distinct finishes - smooth and antique

HEIGHT


65

Millimetres

FINISHES

Sm

Smooth

Ant

Antique


 215 x 65 x
102.5mm

STOCK INFORMATION

Product type	Length (mm)	Depth (mm)	Height (mm)	In Stock	Available Colours	Units per pack	Unit weight (kg)	Weight per pack (t)	Packs per 8 wheeler	Packs per unit lorry
FACING BRICK	215	102.5	65	YES	Durrow Cream Smooth / Durrow Cream Antique / Edenmore Smooth / Edenmore Antique / Lewis Smooth / Lewis Antique / Oldtown Multi Smooth / Oldtown Multi Antique / Shandon Smooth / Shandon Antique	512	2.9	1.55	10	GB 18 / IRE 16
				MTO	Ashbrooke Smooth / Ashbrooke Antique / Clarendon Blue Smooth / Clarendon Blue Antique / Doonmore Smooth / Doonmore Antique / Hampton Smooth / Hampton Antique / Lyndhurst Smooth / Lyndhurst Antique / Olde Dublin Buff Smooth / Olde Dublin Buff Antique / Tullamore Smooth / Tullamore Antique / Vintage White Smooth / Vintage White Antique / Wicklow Smooth / Wicklow Antique					

NB. In stock items requiring over 10,000 no. bricks are treated as made to order.

MTO - made to order (minimum order size 10,000 no. bricks).

All bricks are supplied on pallets.

All size dimensions are nominal.

TECHNICAL INFORMATION

MANUFACTURING STANDARD	hEN 771-3: 2011+A1 : 2015 Attestation Level 2+ Category 1	THERMAL CONDUCTIVITY	1.56 W / m.K
COMPRESSIVE STRENGTH*	Min average 22 N/mm ²	INITIAL RATE OF ABSORPTION	0.42 Kg / m ² .m-1
WATER ABSORPTION (24HR)	6% max	BOND STRENGTH	0.15 N / mm ²
DURABILITY DESIGNATION	F2 Severe Exposure	REACTION TO FIRE	A1 Class
MEAN COEFFICIENT OF WATER ABSORPTION	4.4 g / (m ² .s)	TYPE OF MORTAR	Recommended ratio 6 : 1 or 5 : 1 Sand : OPC
MOISTURE MOVEMENT COEFFICIENT**	0.46 mm / m	WATER VAPOUR PERMEABILITY [u]	5 / 15u tabulated from EN 1745
ACTIVE SOLUBLE SALTS [SO3]	0.03%	PACK QUANTITY	512
SIZE TOLERANCE	hEN 771-3: 2011 (T1) Category D2	PACK SIZE [APX. MM]	L 850 x D 850 x H 1100mm
GROSS DENSITY	2200 Kg / m ³	TYPICAL PACK WEIGHT	1550 Kg
		PACKAGING (FULL SHRINK BAG)	Pallet

* Compressive strength in accordance with PD 6697 : 2010 and Eurocode 6.

** Determination of moisture movement and drying shrinkage carried out in accordance with hEN 772-14:2001 (E)

Enduur 1

Enhanced colour and reduced efflorescence.

Enhanced mix which increases strength, resistance to wear and tear, longevity and vibrance.

30% less embodied carbon than a kiln-fired clay brick.

Helps prevent moss and algae growth and deep staining.

