



Acoustic Impact Assessment:

Coldharbour Road, Gravesend

Simply UK

16th August 2024



Report Details:

Report Title	Acoustic Impact Assessment
Site	Coldharbour Road, Gravesend
Client	Simply UK
Report No.	H4223 – NV – v3

Version History:

Version	Date	Notes	Author	Checked
V1	13 th August 2024	Original Issue	Mathew Vaughan MSc AMIOA	Nick Hawkins MSc MIOA MIAQM
V2	15 th August 2024	Minor Amendments	Mathew Vaughan MSc AMIOA	Nick Hawkins MSc MIOA MIAQM
V3	16 th August 2024	Minor Amendments	Mathew Vaughan MSc AMIOA	Nick Hawkins MSc MIOA MIAQM

This report has been prepared by Hawkins Environmental Limited for the sole purpose of assisting in gaining planning consent for the proposed development described in the introduction of this report.

This report has been prepared by Hawkins Environmental Limited with all reasonable skill, care and diligence, and taking account of the manpower and resources devoted to it by agreement with the client. Information reported herein is based on the interpretation of data collected and has been accepted in good faith as being accurate and valid.

This assessment takes into account the prevailing conditions at the time of the report and assesses the impact of the development (if applicable) using data provided to Hawkins Environmental Limited by third parties. The report is designed to assist the developer in refining the designs for the proposed development and to demonstrate to agents of the Local Planning Authority that the proposed development is suited to its location. This should be viewed as a risk assessment and does not infer any guarantee that the site will remain suitable in future, nor that there will not be any complaints either from users of the development or from impacts emanating from the development site itself.

This report is for the exclusive use by the client named in the report. Hawkins Environmental Limited does not accept any liability in negligence for any matters arising outside of the agreed scope of works.

Unless otherwise agreed, the copyright of this document and all other Intellectual Property Rights remain the property of Hawkins Environmental Limited at all times.

Table of Contents

1.	INTRODUCTION	5
1.1.	Overview	5
1.2.	The Nature, Measurement and Effect of Noise	5
1.3.	Site Description	6
2.	NATIONAL & LOCAL PLANNING POLICY	8
2.1.	National Planning Policy Framework (2023).....	8
2.2.	Noise Policy Statement for England (2010).....	9
2.3.	Planning Practice Guidance	9
3.	ASSESSMENT METHODOLOGY & GUIDANCE.....	13
3.1.	BS 8233: 2014 'Guidance on Sound Insulation and Noise Reduction for Buildings'	13
3.2.	World Health Organisation Guidelines for Community Noise (1999).....	14
3.3.	WHO Night Noise Guidelines for Europe (2009)	15
3.4.	BS 4142: 2014 +A1:2019 Methods for Rating and Assessing Industrial and Commercial Sound	15
3.5.	BS 4142:2014+A1:2019 Technical Note (2020)	16
4.	SOUND MEASUREMENT STUDY	20
4.1.	Overview	20
4.2.	Background Sound Levels.....	21
5.	IMPACT OF THE PLANT	26
5.1.	Overview	26
5.2.	Proposed Plant.....	26
5.3.	Specific and Rating Sound Level.....	26
5.4.	Adherence to Sound Criteria	28
6.	OVERALL CONCLUSIONS AND RECOMMENDATIONS	29

List of Appendices

Appendix 1 Glossary of Acoustic Terms	30
Appendix 2 Schedule of Equipment	32
Appendix 3 Summary of Sound Measurements	40
Appendix 4 Substation Data from Manufacturer	42

List of Tables

Table 1.1: Typical Noise Levels	6
Table 2.1: Noise Exposure Hierarchy	12
Table 3.1: Summary of Noise Criteria: BS 8233: 2014	13
Table 3.2: Summary of Noise Criteria: WHO	15
Table 4.1: Summary of Weather Conditions during the Sound Measurements	20
Table 4.2: Summary of the Sound Level Measurements	22
Table 5.1: Plant Sound Power Levels	26
Table 5.2: Receptor Specific Sound Levels	26
Table 5.3: Subjective Character Corrections	27
Table 5.4: Receptor Rating Sound Levels	28
Table 5.5: BS 4142 Assessment	28

List of Figures

Figure 4.1: Noise Measurement Location	21
Figure 4.2: Noise Measurements	23
Figure 4.3: Distribution of Day Time $L_{A90,1\text{hour}}$ Sound Levels	24
Figure 4.4: Distribution of Night-Time $L_{A90,15\text{mins}}$ Sound Levels	25
Figure 5.1: Locations of the Sensitive Receptors and Plant	27

1. INTRODUCTION

1.1. Overview

Hawkins Environmental Limited has been instructed by Simply UK, to undertake an acoustic impact assessment for a proposed new electrical substation at a new care home situated along Coldharbour Road in Gravesend, Kent.

1.1.1. Criteria

During the planning process, it has been identified that the site may require a noise assessment to determine whether noise emissions from the proposed electrical substation would be in line with permitted levels. Consequently, a noise survey was conducted to characterise the noise climate of the site and the impact of the proposed new plant has been assessed.

The assessment adheres to the principles of Government planning policy in relation to noise, specifically enacted by the *National Planning Policy Framework (NPPF)*, the *National Planning Practice Guidance (NPPG) on Noise* and the *Noise Policy Statement for England (NPSE)*.

All sound measurements were conducted in accordance with BS 7445-2: 1991 '*Description and measurement of environmental noise Part 2: Guide to the acquisition of data pertinent to land use*'. The assessment of plant sound has been assessed in accordance with British Standard BS 4142: 2014 +A1:2019 '*Methods for rating and assessing industrial and commercial sound*'.

1.2. The Nature, Measurement and Effect of Noise

Noise is often defined as sound that is undesired by the recipient. Whilst it is impossible to measure nuisance caused by noise directly, it is possible to measure the loudness of that noise. 'Loudness' is related to both sound pressure and frequency, both of which can be measured. The human ear is sensitive to a wide range of sound levels. The sound pressure level of the threshold of pain is over a million times that of the quietest audible sound. In order to reduce the relative magnitudes of the numbers involved, a logarithmic scale of decibels (dB) is normally used, based on a reference level of the lowest audible sound.

The response of the human ear is not constant over all frequencies. It is therefore usual to weight the measured frequencies to approximate the human response. The resulting 'A' weighted decibel, dB(A), has been shown to correlate closely to the subjective human response.

When related to changes in noise, a change of ten decibels from say 60 dB(A) to 70 dB(A) would represent a doubling in 'loudness'. Similarly, a decrease in noise from 70 dB(A) to 60 dB(A) would represent a halving in 'loudness'. A change of 3 dB(A) is generally considered to be just perceptible. **Table 1.1** details typical noise levels. A glossary of acoustic terms can be found in **Appendix 1**.

Table 1.1: Typical Noise Levels

Approximate Noise Level (dB(A))	Example
0	Limit of hearing
30	Rural area at night
40	Library
50	Quiet office
60	Normal conversation at 1 m
70	In car noise without radio
80	Household vacuum cleaner at 1 m
100	Pneumatic drill at 1 m
120	Threshold of pain

1.3. Site Description

The development site is situated along Coldharbour Road in Northfleet, Gravesend. The site currently comprises a derelict and vacant site associated with the former demolished Battle of Britain public house. The proposed development will see the construction of a care home comprising of 75 bedrooms featuring new landscaping and private parking space in addition to a new electrical substation. A location plan of the proposed site can be seen in **Figure 1.1**.

Figure 1.1: Site Location Plan



2. NATIONAL & LOCAL PLANNING POLICY

2.1. National Planning Policy Framework (2023)

The National Planning Policy Framework (NPPF) was first published on the 27th March 2012 and revised July 2018, February 2019, July 2021 and September 2023, with the latest version published in December 2023 in response to the Levelling-up and Regeneration Bill.

The NPPF outlines the Government's planning policies for England and determines how they should be applied. It provides a framework within which Local Planning Authorities are required to prepare their own locally-prepared plans, where both the policies within the NPPF and the local plan are material planning considerations against which planning decisions are determined. These distinctive local and neighbourhood plans should be interpreted and applied in order to meet the needs and priorities of their communities.


The NPPF notes *"The purpose of the planning system is to contribute to the achievement of sustainable development, including the provision of homes, commercial development, and supporting infrastructure in a sustainable manner"* (Paragraph 7). The NPPF notes sustainable development should be delivered with three main dimensions: economic; social and environmental (Paragraph 8).

The NPPF supports a presumption in favour of development, unless the adverse impacts of that development outweighs the benefits it notes *"that sustainable development is pursued in a positive way, at the heart of the Framework is a presumption in favour of sustainable development"* (Paragraph 10).

The NPPF states that in the planning system *"Planning policies and decisions should contribute to and enhance the natural and local environment by... e) preventing new and existing development from contributing to, being put at unacceptable risk from, or being adversely affected by, unacceptable levels of soil, air, water or noise pollution or land instability. Development should, wherever possible, help to improve local environmental conditions such as air and water quality, taking into account relevant information such as river basin management plans"* (Paragraph 180).

Paragraph 191 of the NPPF talks specifically about noise stating that *"Planning policies and decisions should also ensure that new development is appropriate for its location taking into account the likely effects (including cumulative effects) of pollution on health, living conditions and the natural environment, as well as the potential sensitivity of the site or the wider area to impacts that could arise from the development. In doing so they should: a) mitigate and reduce to a minimum potential adverse impacts resulting from noise from new development – and avoid noise giving rise to significant adverse impacts on health and the quality of life; b) identify and protect tranquil areas which have remained relatively undisturbed by noise and are prized for their recreational and amenity value for this reason..."*

Specifically in relation to noise from existing commercial premises, Paragraph 193 of the NPPF notes: *"Planning policies and decisions should ensure that new development can be integrated effectively with existing businesses and community facilities (such as places of worship, pubs, music venues and sports clubs). Existing businesses and facilities should not have unreasonable restrictions placed on them as a result of development"*



permitted after they were established. Where the operation of an existing business or community facility could have a significant adverse effect on new development (including changes of use) in its vicinity, the applicant (or 'agent of change') should be required to provide suitable mitigation before the development has been completed".

2.2. Noise Policy Statement for England (2010)

The Noise Policy Statement for England (NPSE) provides further guidance on the interpretation of Section 123 of the NPPF and states that: *"Within the context of sustainable development:*

- avoid significant adverse impacts on health and quality of life;
- mitigate and minimise adverse impacts on health and quality of life; and
- where possible contribute to the improvement of health and quality of life."

NPSE introduces established concepts originally from the field of toxicology that are now being applied to noise impacts. They are:

- **NOEL – No Observed Effect Level** - This is the level of noise below which no effect can be detected. In simple terms, below this level, there is no detectable effect on health and quality of life due to the noise.
- **LOAEL – Lowest Observed Adverse Effect Level** - This is the level of noise above which adverse effects on health and quality of life can be detected.
- **SOAEL – Significant Observed Adverse Effect Level** - This is the level above which significant adverse effects on health and quality of life occur.



NPSE goes on to state that *"it is not possible to have a single objective noise-based measure that defines SOAEL that is applicable to all sources of noise in all situations. Consequently, the SOAEL is likely to be different for different noise sources, for different receptors and at different times. It is acknowledged that further research is required to increase our understanding of what may constitute a significant adverse impact on health and quality of life from noise. However, not having specific SOAEL values in the NPSE provides the necessary policy flexibility until further evidence and suitable guidance is available."*

2.3. Planning Practice Guidance

The Planning Practice Guidance was launched on 6th March 2014 and provides additional guidance and interpretation to the Government's strategic policies, outlined within the NPPF, in a web-based resource. This is updated regularly.

The NPPG provides more guidance on the assessment of noise for planning purposes and builds on the concepts of NOEL, LOAEL and SOAEL introduced in NPSE to establish whether noise is a factor that needs to be taken into account. It states: *"Local planning authorities' plan-making and decision taking should take account of the acoustic environment and in doing so consider:*

- *whether or not a significant adverse effect is occurring or likely to occur;*



- whether or not an adverse effect is occurring or likely to occur; and
- whether or not a good standard of amenity can be achieved.

In line with the Explanatory Note of the Noise Policy Statement for England, this would include identifying whether the overall effect of the noise exposure (including the impact during the construction phase wherever applicable) is, or would be, above or below the significant observed adverse effect level and the lowest observed adverse effect level for the given situation.”

However, it goes into more detail about the subjective nature of noise and how the results of any assessment must be treated flexibly and pragmatically. The guidance states: “*The subjective nature of noise means that there is not a simple relationship between noise levels and the impact on those affected. This will depend on how various factors combine in any particular situation. These factors include:*

- *the source and absolute level of the noise together with the time of day it occurs. Some types and level of noise will cause a greater adverse effect at night than if they occurred during the day – this is because people tend to be more sensitive to noise at night as they are trying to sleep. The adverse effect can also be greater simply because there is less background noise at night;*
- *for non-continuous sources of noise, the number of noise events, and the frequency and pattern of occurrence of the noise;*
- *the spectral content of the noise (ie whether or not the noise contains particular high or low-frequency content) and the general character of the noise (ie whether or not the noise contains particular tonal characteristics or other particular features). The local topology and topography should also be taken into account along with the existing and, where appropriate, the planned character of the area.*

More specific factors to consider when relevant include:

- *the cumulative impacts of more than one source of noise;*
- *whether any adverse internal effects can be completely removed by closing windows and, in the case of new residential development, if the proposed mitigation relies on windows being kept closed most of the time (and the effect this may have on living conditions). In both cases a suitable alternative means of ventilation is likely to be necessary. Further information on ventilation can be found in the Building Regulations.*
- *In cases where existing noise sensitive locations already experience high noise levels, a development that is expected to cause even a small increase in the overall noise level may result in a significant adverse effect occurring even though little to no change in behaviour would be likely to occur.*
- *Noise Action Plans (where these exist), and, in particular the Important Areas identified through the process associated with the Environmental Noise Directive and corresponding regulations should be taken into account. Defra’s website has information on Noise Action Plans and Important Areas. Local authority environmental health departments will also be able to provide information about Important Areas.*

- *the effect of noise on wildlife. Noise can adversely affect wildlife and ecosystems. Particular consideration needs to be given to the potential effects of noisy development on international, national and locally designated sites of importance for biodiversity;*
- *where external amenity spaces are an intrinsic part of the overall design, the acoustic environment of those spaces should be considered so that they can be enjoyed as intended.*
- *some commercial developments including restaurants, hot food takeaways, night clubs and public houses can have particular impacts, not least because activities are often at their peak in the evening and late at night. Local planning authorities will wish to bear in mind not only the noise that is generated within the premises but also the noise that may be made by customers in the vicinity”.*

Table 2.1 shows examples of the noise hierarchy (adapted from the PPG) and shows that the aim is to identify where the overall effect of the noise exposure falls in relation to SOAEL, LOAEL and NOEL. The implication of the advice is that only noise that is ‘noticeable and very disruptive’ would be considered unacceptable and therefore, should be prevented. The inference, therefore, is that all other outcomes can be acceptable, depending upon the specific circumstances and level of mitigation.

Table 2.1: Noise Exposure Hierarchy

Perception	Examples of outcomes	Increasing effect level	Action	
Not noticeable	No Effect	No Observed Effect	No specific measures required	Low Noise Level
Noticeable and not intrusive	Noise can be heard but does not cause any change in behaviour or attitude. Can slightly affect the acoustic character of the area but not such that there is a perceived change in the quality of life.	No Observed Adverse Effect	No specific measures required	
Lowest Observed Adverse Effect Level				
Noticeable and intrusive	Noise can be heard and causes small changes in behaviour and/or attitude, eg turning up the volume of television; speaking more loudly; where there is no alternative ventilation, having to close windows for some of the time because of the noise. The potential for some reported sleep disturbance. Affects the acoustic character of the area such that there is a perceived change in the quality of life.	Observed Adverse Effect	Mitigate and reduce to a minimum	
Significant Observed Adverse Effect Level				
Noticeable and disruptive	The noise causes a material change in behaviour and/or attitude, eg avoiding certain activities during periods of intrusion; where there is no alternative ventilation, having to keep windows closed most of the time because of the noise. The potential for sleep disturbance resulting in difficulty in getting to sleep, premature awakening and difficulty in getting back to sleep.	Significant Observed Adverse Effect	Avoid	
Noticeable and very disruptive	Extensive and regular changes in behaviour and/or an inability to mitigate the effect of noise leading to psychological stress or physiological effects, eg regular sleep deprivation/awakening; loss of appetite, significant, medically definable harm, eg auditory and non-auditory	Unacceptable Adverse Effect	Prevent	High Noise Level

Increasing Noise Levels
↓


3. ASSESSMENT METHODOLOGY & GUIDANCE

3.1. BS 8233: 2014 ‘Guidance on Sound Insulation and Noise Reduction for Buildings’

Originally published in 1999, the 2014 edition of BS 8233, significantly updates the guidance in light of the policy changes as a result of the advent of the NPPF and the withdrawal of PPG 24. The 2014 edition of BS 8233 sees a change in the title of the Standard, moving from a ‘Code of Practice’ to ‘Guidance’, as the text ‘largely comprises guidance that does not support claims of compliance’.

BS 8233:2014 indicates that to control external noise ingress into a proposed development, a number of planning stages should occur as follows:

- “Assess the site, identify significant existing and potential noise sources, measure or estimate noise levels, and evaluate layout options.
- Determine design noise levels for spaces in and around the building(s).
- Determine sound insulation of the building envelope, including the ventilation strategy”.



BS 8233:2014 suggests design noise levels for various types of building. The recommended noise levels for dwelling houses, flats and rooms in residential use (when unoccupied) can be seen in **Table 3.1** below. This is replicated from Table 4 of Section 7.7.2 of BS 8233:2014. The guidance suggests that “In general, for steady external noise sources, it is desirable that the internal ambient noise level does not exceed the guideline values”. The noise levels in **Table 3.1** are marginally different to those published in BS 8233:1999 ‘Sound insulation and noise reduction for buildings – Code of practice’, but are based on the existing guidance from the current World Health Organisation (WHO) “Guidelines on Community Noise”.

Table 3.1: Summary of Noise Criteria: BS 8233: 2014

Activity	Location	07:00 To 23:00	23:00 To 07:00
Resting	Living room	35 dB L _{Aeq,16hour}	-
Dining	Dining room/area	40 dB L _{Aeq,16hour}	-
Sleeping	Bedroom	35 dB L _{Aeq,16hour}	30 dB L _{Aeq,8hour}

When considering the noise level criteria considered in **Table 3.1**, the following points should be noted:

- BS 8233: 2014 suggests that the above criteria should be adopted flexibly and that “where development is considered necessary or desirable... the internal target level may be relaxed by up to 5 dB and reasonable internal conditions still achieved”.
- The noise levels quoted above are annual averages and “do not need to be achieved in all circumstances” e.g. New Year’s Eve or fireworks night.

- The noise levels in **Table 3.1** are “for steady external noise sources” such as traffic noise or plant noise. This is a departure from the 1999 version of BS 8233, where the recommended internal noise levels were irrespective of the external noise source and therefore included the suggestion that in order to achieve “reasonable” noise levels within bedrooms at night, L_{AFmax} noise levels should not exceed 45 dB. Whilst this has been omitted from the 2014 version of BS 8233, it does state that “Regular individual noise events (for example, scheduled aircraft or passing trains) can cause sleep disturbance. A guideline value may be set in terms of SEL or $L_{Amax,F}$, depending on the character and number of events per night. Sporadic noise events could require separate values.” Therefore, at sites which may be affected by individual noise events, it is more appropriate to use the guidance contained within the WHO “Guidelines on Community Noise” which suggest that good sleep will not generally be affected if internal levels of L_{AFmax} 45 dB are not exceeded more than 10-15 times per night.
- BS 8233:2014 notes that if the design of the building is “relying on closed windows to meet the guide values, there needs to be appropriate alternative ventilation that does not compromise the facade insulation or resulting noise level”.
- BS 8233 provides guidance for noise in gardens and outdoor amenity space. It suggests that “it is desirable that the external noise level does not exceed 50 dB $L_{Aeq,T}$, with an upper guideline value of 55 dB $L_{Aeq,T}$ which would be acceptable in noisier environments.” The guidance does go on to say that these guideline values are not achievable in all circumstances and in some areas, “such as city centres or urban areas adjoining the strategic transport network, a compromise between elevated noise levels and other factors, such as the convenience of living in these locations or making efficient use of land resources to ensure development needs can be met, might be warranted. In such a situation, development should be designed to achieve the lowest practicable levels in these external amenity spaces, but should not be prohibited.”

3.2. World Health Organisation Guidelines for Community Noise (1999)

The 1999 World Health Organisation (WHO) guidance “Guidelines for Community Noise”, provides recommendations on maximum internal and external noise levels in a range of situations. The WHO guidelines are a consequence of a comprehensive review of the scientific evidence in relation to community noise exposure and the health and social aspects of such exposure. Whilst not adopted policy, the recommendations within the WHO Guidelines are often quoted and form the basis of the recommendations within BS 8233 and other similar guidance. A summary of the noise criteria can be seen in **Table 3.2**.





Table 3.2: Summary of Noise Criteria: WHO

Residential Environment	Critical Health Effect	L_{Aeq}	L_{AFmax}	Time Base
Outdoor living area	Serious annoyance, daytime and evening	55	-	07:00-23:00
	Moderate annoyance, daytime and evening	50	-	07:00-23:00
Dwelling, indoors	Speech intelligibility and moderate annoyance, daytime and evening	35	-	07:00-23:00
Inside bedrooms	Sleep disturbance, night-time	30	45	23:00-07:00
Outside bedrooms	Sleep disturbance, window open (outdoor values)	45	60	23:00-07:00

3.3. WHO Night Noise Guidelines for Europe (2009)

In 2009, the World Health Organisation published the “Night Noise Guidelines for Europe” as a partial update and extension to the “Guidelines for Community Noise”, specifically in relation to development on the scientific evidence of night noise exposure. The 2009 guidance suggests that a “ $L_{night,outside}$ of 40 dB should be the target of the night noise guideline (NNG) to protect the public, including the most vulnerable groups such as children, the chronically ill and the elderly”. However, since that target would be impossible to achieve in many situations, a “ $L_{night,outside}$ value of 55 dB is recommended as an interim target for the countries where the NNG cannot be achieved in the short term for various reasons, and where policy-makers choose to adopt a stepwise approach”.




3.4. BS 4142: 2014 +A1:2019 Methods for Rating and Assessing Industrial and Commercial Sound

British Standard BS 4142: 2014 +A1:2019 “Methods for rating and assessing industrial and commercial sound” provides a method for the measurement and rating of industrial noise or noise of an industrial nature and background noise levels outside dwellings in mixed residential and industrial areas. The rating level (defined in the BS) is used to rate the industrial noise source outside residential dwellings (this is defined as the “specific noise source”).

The procedure defined in BS 4142 for predicting the likelihood of complaints is based on establishing the difference between the rating level and the background level outside the residential property of interest. The greater the difference the greater the likelihood of complaints and more specifically:

- “A difference of around +10 dB or more is likely to be an indication of a significant adverse impact, depending on the context;



- A difference of around +5 dB is likely to be an indication of an adverse impact, depending on the context;
- The lower the rating level is relative to the measured background sound level, the less likely it is that the specific sound source will have an adverse impact or a significant adverse impact. Where the rating level does not exceed the background sound level, this is an indication of the specific sound source having a low impact, depending on the context.
- Adverse impacts include, but are not limited to, annoyance and sleep disturbance. Not all adverse impacts will lead to complaints and not every complaint is proof of an adverse impact.”

The guidance goes on to state that “where background sound levels and rating levels are low, absolute levels might be as, or more, relevant than the margin by which the rating level exceeds the background. This is especially true at night.” Consequently, when considering the impact of a BS 4142 assessment, it is often also necessary to consider the absolute noise levels experienced at the receptor location in relation to BS 8233 and World Health Organisation guidelines.

3.5. BS 4142:2014+A1:2019 Technical Note (2020)

In March 2020, Acoustic and Noise Consultants (the ANC) published a guidance note to accompany BS 4142.

The Technical Note states “remain concerns for some users of BS 4142 and this guidance is designed to assist readers with a reasonable interpretation and application of BS 4142 as a whole”. It notes “In the production of this guidance, the ANC Working Group (WG) has reviewed BS 4142 and attempted to address any content regarded as ambiguous”. Consequently, whilst not an official guidance document, the Technical Note provides advice of the interpretation of BS 4142 and provides examples of best practice with regards to the application of the BS.



The following sub-sections contain clarifications from the Technical Note that are particularly pertinent to this assessment.

3.5.1. Internal Noise Levels

The Technical Note notes “BS 4142 ‘is not intended to be applied to the assessment of indoor sound levels’ (Subclause 1.3) and cannot, therefore, be used for façade design. Whilst BS 4142 can be used to assist in the determination of the likelihood of an adverse or significant adverse impact, guidance on internal design criteria and mitigation is provided elsewhere”. The Technical Note goes on to state that in conjunction with BS 4142, the use of BS 8233 may be appropriate to determine internal noise levels “although recognition should be given to the associated scope and/or limitations”.

3.5.2. Introduction of a New Noise-Sensitive Receptors

One of the major short-comings of BS 4142 is the lack of differentiation between the assessment of new noise sources verses the assessment of new noise-sensitive receptors. Subclause 8.5 of BS 4142 states “Where a new noise-sensitive receptor is introduced and there is extant industrial and/or commercial sound, it ought to be recognized that the industrial and/or commercial sound forms a component of the acoustic environment. In

such circumstances other guidance and criteria in addition to or alternative to this standard can also inform the appropriateness of both introducing a new noise-sensitive receptor and the extent of required noise mitigation”.

The Technical Note clarifies this position by noting “*where BS 4142 is used in this situation, its fundamental principles, in terms of what constitutes the residual, background and specific sources, should not be compromised. Where other standards or guidance document are used, care should be taken with regard to their own stated scope or limitations. Examples of such guidance might include:*

- *BS8233: 2014 where an industrial/commercial sound source is constant and new residential development is proposed nearby;*
- *Elements of ProPG where the impact of regular night time maximum sound events is the critical consideration;*
- *DMRB where impacts relate solely to changes to vehicular movements within or around a site; or*
- *BS 5228 where activities are temporary and of a similar nature to the construction activities considered by that Standard.*

These documents, or others, may help to inform the contextual elements of a BS 4142 assessment or help where a numerical assessment fully in accordance with BS 4142 may not be possible”.

In this regard the Technical Note that when assessing new noise-sensitive receptors close to commercial noise sources, it may not be possible to use BS 4142 as difficulties in disaggregating “*legitimate commercial residual sources to the background sound level could potentially lead to unrepresentatively adverse outcomes*”. Consequently, “*alternative guidance and standards should be referenced, although care should be taken not to apply them beyond their own stated scope or limitations*”. It goes on to note that “*different approaches might be adopted depending on whether the industrial/commercial source is continuous or intermittent, whether there are ancillary sources present, or where one particular industrial/commercial premises dominates*”.

3.5.3. Background Sound Levels

BS 4142 does not provide a definitive method for calculating or determining a background sound level. The Technical Note does not a definitive method either, but does provide more clarification. It notes “*it was the view of the WG that it is not always appropriate to define a singular background sound level for use in an assessment. In such cases, a range of values over one or more time periods may be more appropriate. An assessment should generally focus on the sound levels measured during the period of greatest interest, which may be the quietest part of the night, or the time period relating to a complaint. Determining the period of greatest interest should be judged on a case-by-case basis*”.

The Note points out that “*it is important that the established background sound level is representative of typical conditions*”. It goes on to provide a number of examples whereby time history, histogram and cumulative distribution data is presented, along with the range of values selected by the WG as being representative. “*These examples are included to illustrate the range of views in the WG as to how best to identify representative background sound levels for particular datasets and serve to highlight the sensitivity of the outcome to individual interpretations of measurement data. It must be remembered that there are no ‘correct’ answers, only judgement and justification. In many instances, additional information beyond that presented in these examples would be required to inform the judgement of representative levels*”.

3.5.4. Context

The criteria used to determine the acceptability of an impact with BS 4142 talks about the requirement to consider “context”. However, BS 4142 does not provide much detail as to what one might consider in relation to context.

BS 4142 notes that absolute levels of sound can be of significance, where residual values are both high and low. In particular, BS 4142 notes that absolute levels may be as, or more, important than relative outcomes where background and rating levels are low, but does not provide further commentary.

The Technical Note points out that “BS 4142 does not indicate how the initial estimate of impact should be adjusted when background and rating levels are low, only that the absolute levels may be more important than the difference between the two values. It is likely that where the background and rating levels are low, the absolute levels might suggest a more acceptable outcome than would otherwise be suggested by the difference between the values. For example a situation might be considered acceptable where a rating level of 30dB is 10dB above a background sound level of 20dB, i.e. an initial estimate of a significant adverse impact is modified by the low rating and background sound levels.

There may be situations where the opposite is true, and it is for the assessor to justify any modifications to the initial estimate of impact.

BS 4142 does not define ‘low’ in the context of background sound levels nor rating levels. The note to the Scope of the 1997 version of BS 4142 defined very low background sound levels as being less than about 30 dB L_{A90} , and low rating levels as being less than about 35 dB $L_{A,T,r}$.

The WG suggest that similar values would not be unreasonable in the context of BS 4142, but that the assessor should make a judgement and justify it where appropriate”.

The Technical Note suggests other areas one might consider when looking at context:

- “character of a particular neighbourhood;
- former uses at or close to a site;
- legitimacy of the industrial use, e.g. planning permissions or environmental permits;
- implementation of best practicable means for a given process or activity; or
- local convention or perceptions”.

It goes on to provide two examples:

“For example; a former industrial use may be less relevant if it ceased 10 years previously, than a use that ceased within the previous six months. Setting out the context in this way is important so that the reader is fully aware of the point being made”.

“For example; a coffee shop with drive thru facility located adjacent to a fairly busy road with traffic lights and constant stop/start traffic, with residential properties nearby. In these circumstances the noise climate is unlikely to change in any perceptible way due to the addition of vehicles moving and idling in the drive thru area. However, during the evening, the gaps in the general traffic could reduce the background sound level sufficiently that an adverse or significant adverse impact is suggested. An intermittency correction could also be

considered appropriate. In this example, the assessor might legitimately take the view that the context is at odds with the initial (numerical) assessment, and substantially adjust the conclusions of the assessment on the basis of the context”.

4. SOUND MEASUREMENT STUDY

4.1. Overview

In order to determine the extent to which the site is affected by sound, a detailed sound measurement study has been carried out on the proposed development site. Sound measurements have been carried out in order to determine the background sound levels for the day and night time periods.

All noise monitoring was conducted using a Norsonic 140 sound level meter, which conforms to BS EN IEC 61672-1: 2003 as a Class 1 precision measurement system. A Norsonic 1251 field calibrator was used before and after the measurement periods in order to ensure that the equipment had remained within reasonable calibration limits (+/- 0.5 dB).

All of the equipment used has been calibrated in accordance with the procedures set out in BS EN IEC 61672-2: 2003 and for the electrical testing of frequency filters as set out in BS EN IEC 61260. The equipment was calibrated at Campbell Associates Limited, in Great Dunmow, Essex. Campbell Associates Limited meets the laboratory accreditation requirements of the United Kingdom Accreditation Service (UKAS Lab No. 0789). Sound level meters are laboratory calibrated every two years, with field calibrators laboratory calibrated every twelve months. **Appendix 2** summarises the equipment used including serial numbers and calibration certificates.

All noise monitoring has been conducted in accordance with the guidance set out in BS 7445-2: 1991 '*Description and measurement of environmental noise Part 2: Guide to the acquisition of data pertinent to land use*'. This standard details information that should be recorded in addition to the actual measured levels such as meteorological data, and a description of the noise source itself.

The survey was conducted on the 5th and 6th of April 2022. The noise monitoring was conducted by Mathew Vaughan of Hawkins Environmental Limited. Mathew is an Associate Member of the Institute of Acoustics and holds a Masters of Science in Applied Acoustics from Solent University.

Weather conditions were conducive to successful monitoring. **Table 4.1** summarises the weather conditions during the measurement period.

Table 4.1: Summary of Weather Conditions during the Sound Measurements

General Description	The measurement periods were warm for the time of year, with some sunshine during the day with light winds.
Windspeed	Average wind speeds were low, typically less than 5 m/s.
Temperature	The temperature went down to around 9°C at night, with daytime temperatures up to 15°C.
Precipitation	The measurement period remained dry, with the exception of a very brief light rain shower around 8am. However, the noise measurement results appear to be unaffected by this brief shower.

4.2. Background Sound Levels

BS 4142: 2014 +A1:2019 'Methods for rating and assessing industrial and commercial sound' requires the determination of background sound levels at a location representative of the potentially affected receptors.

Sound measurements were conducted at location within the proposed development site, situated at a location marked on **Figure 4.1**. It is considered that background noise measurements conducted at this location will be representative of the surrounding dwellings. The sound monitoring location was considered to be a freefield location.

Figure 4.1: Noise Measurement Location



Noise Measurement Location

It is understood that the proposed electrical substation would operate at any time. Consequently, background noise measurements have been conducted over a typical 24-hour period. The noise measurement data is detailed in **Appendix 3** and summarised in **Figure 4.2** and **Table 4.2**.

Table 4.2: Summary of the Sound Level Measurements

Period (hours)	Measured Facade Sound Level dB			
	$L_{Aeq,T}$	Range $L_{Aeq,15mins}$	Range $L_{Amax,15mins}$	Range $L_{A90,15mins}$
7am to 11pm	67.7	62.7 – 73.5	73.3 – 99.2	47.4 – 62.8
11pm to 7am	62.4	49.2 – 73.6	67.0 – 101.5	42.5 – 56.6

The background sound levels have been calculated in accordance with BS 4142:2014, which represents the most up-to-date guidance on the subject. Prior to the publication of the 2014 version of BS 4142, acousticians would use the lowest measured background sound levels; however, BS 4142: 2104 provides substantially more guidance on the determination of background sound levels. Section 8.1 of BS 4142: 2014 states that “*for this purpose, the objective is not simply to ascertain a lowest measured background sound level, but rather to quantify what is typical during particular time periods. Among other considerations, diurnal patterns can have a major influence on background sound levels and, for example, the middle of the night can be distinctly different (and potentially of lesser importance) compared to the start or end of the night-time period for sleep purposes*”. The guidance goes on to say that “*a representative level ought to account for the range of background sound levels and ought not automatically to be assumed to be either the minimum or modal value*”.

In order to determine the background sound levels for the night-time periods, the background sound levels have been analysed over the appropriate time periods, i.e. 15 minutes for night-time (11 pm to 7 am) and 1 hour for the daytime periods. **Figure 4.4** and **Figure 4.5** details the distribution of the background sound levels as described in BS 4142: 2014 for the day and night-time periods respectively.

It can be seen from **Figure 4.4** that during the day, the $L_{A90,1hour}$ ranged from 50 dB to 60 dB. It can be seen from the data in **Appendix 3** that between 7am and 7pm, background noise levels were consistently between 57 and 59 dB; therefore, between these hours 58 dB would be considered to be the background noise level. However, in the evening period up to 11pm, 50 dB may be a more representative background noise level.

It can be seen from **Figure 4.5** that during the night, the $L_{A90,15mins}$ ranged from 43 dB to 56 dB, with the largest number at 44 dB. To characterise a worst-case scenario in terms of night-time background noise levels, it is considered that 44 dB is the night-time background noise level.

Acoustic Impact Assessment:
Coldharbour Road, Gravesend

Simply UK • 16th August 2024 • H4223 • NV • v3

Figure 4.2: Noise Measurements




Figure 4.3: Distribution of Day Time $L_{A90,1\text{hour}}$ Sound Levels





Figure 4.4: Distribution of Night-Time $L_{A90,15mins}$ Sound Levels



5. IMPACT OF THE PLANT

5.1. Overview

The assessment is carried out in accordance with BS 4142:2014+A1:2019 'Methods for rating and assessing industrial and commercial sound'.

5.2. Proposed Plant

At the proposed development, it is proposed to install a 500 kVA EcoDesign Tier 2 electrical substation manufactured by Schneider Electric. According to the manufacturers data, broadband sound power levels can be seen below in **Table 5.1**. Additional data is presented in **Appendix 4**.

Table 5.1: Plant Sound Power Levels

Type	Manufacturer	Model	Sound Power Level (L _{WA}), dB
Substation	Schneider Electric	EcoDesign Tier 2 – 500 kVA	60.0


5.3. Specific and Rating Sound Level

Using the locations of the proposed substation and the published sound power levels of **Table 5.1**, the specific sound level from the plant has been calculated for the nearest two noise sensitive receptors. **Figure 5.1** shows the location of the closest receptors. **Table 5.2** shows the calculated sound levels for this locations based on standard point source distance attenuation.

Table 5.2: Receptor Specific Sound Levels

Rec. ID	Location	Freefield Specific Sound Level in dB(A)
1	Bedroom G-09	6
2	Bedroom 2-01	9
3	1-2 St. Clements Close	4
4	84 New House Lane	6

Figure 5.1: Locations of the Sensitive Receptors and Plant



In accordance with Section 9 of BS 4142, the rating sound level is calculated by applying a character correction to the calculated receiver sound level. For this assessment, the character correction was specified using the “Subjective Method”, where it is necessary to “consider the subjective prominence of the character of the specific sound at the noise-sensitive locations and the extent to which such acoustically distinguishing characteristics will attract attention.” BS 4142 goes on to highlight the subjective correction that one could apply; these corrections are summarised in **Table 5.3** below:

Table 5.3: Subjective Character Corrections

Category	Comments
Tonality	“2 dB for a tone which is just perceptible at the noise receptor, 4 dB where it is clearly perceptible, and 6 dB where it is highly perceptible”.
Impulsivity	“a penalty of 3 dB for impulsivity which is just perceptible at the noise receptor, 6 dB where it is clearly perceptible, and 9 dB where it is highly perceptible”
Other sound characteristics	“Where the specific sound features characteristics that are neither tonal nor impulsive, though otherwise are readily distinctive against the residual acoustic environment, a penalty of 3 dB can be applied.”
Intermittency	“If the intermittency is readily distinctive against the residual acoustic environment, a penalty of 3 dB can be applied.”

The substation is not anticipated to be perceptible to the nearest noise sensitive receptors. Consequently, the rating sound levels are considered equivalent to the specific sound levels. **Table 5.4** determines the rating sound levels at the receptor locations.

Table 5.4: Receptor Rating Sound Levels

Rec. ID	Location	Freefield Rating Sound Level in dB(A)
1	Bedroom G-09	6
2	Bedroom 2-01	9
3	1-2 St. Clements Close	4
4	84 New House Lane	6

5.4. Adherence to Sound Criteria

To assess the impact of the proposed plant, the predicted sound levels have been compared to the criteria in BS 4142. **Table 5.5** below considers the sound levels in a BS 4142 assessment during the period when the plant will be operational. In a BS 4142 assessment, the 'industrial' sound is rated by comparison against the background sound level. The difference between the rating sound level and lowest background sound level gives an indication of the likelihood of complaint.

Table 5.5: BS 4142 Assessment

Receptor	Background Sound Level L_{A90}	Specific Sound Level L_{Aeq}	Rating Sound Level L_{Aeq}	Difference between Rating and Background Sound Levels
1 - Bedroom G-09	44	6	6	-38
2 - Bedroom 2-01	44	9	9	-35
3 - 1-2 St. Clements Close	44	4	4	-40
4 - 84 New House Lane	44	6	6	-38

Note: All sound levels are freefield sound measurements.

BS 4142: 2014 suggests that “The lower the rating level is relative to the measured background sound level, the less likely it is that the specific sound source will have an adverse impact or a significant adverse impact. Where the rating level does not exceed the background sound level, this is an indication of the specific sound source having a low impact, depending on the context”. Consequently, it is possible to conclude that unmitigated, the proposed electrical substation is unlikely to be audible to the residential receptors of the proposed care home in addition to the nearest noise sensitive dwellings at 1-2 St. Clements Close and 84 New House Lane. Therefore, this is an indication that complaints would be unlikely.

6. OVERALL CONCLUSIONS AND RECOMMENDATIONS

A detailed sound measurement study has been carried out to determine whether a proposed electrical substation is likely to be acceptable in terms of noise and whether complaints are considered likely.

Using the guidance and calculation methods contained within BS 4142:2014+A1:2019 '*Methods for rating and assessing industrial and commercial sound*', the rating sound level has been calculated to be at least 35 dB lower than the background sound level. Consequently, it is possible to conclude that unmitigated, the proposed electrical substation would have a low impact on the proposed care home, 1-2 St. Clements Close and 84 New House Lane. Therefore, this suggests that the electrical substation is unlikely to be a constraint upon the development of the site where noise complaints in relation to the electrical substation would be unlikely.

Appendix 1 Glossary of Acoustic Terms

Appendix 1: Glossary of Acoustic Terms

Decibel (dB)	This is a tenth (deci) of a bel. Decibel can be a measure of the magnitude of sound, changes in sound level and a measure of sound insulation. Decibels are not an absolute unit of measurement but are an expression of the ratio between two quantities expressed in logarithmic form.
dB(A)	A-weighted decibels, i.e. decibel level incorporating a frequency weighting (A-weighting), which differentiates between sounds of different frequency (pitch) in a similar way to the human ear. Measurements in dB(A) broadly agree with people's assessment of loudness.
Freefield	A situation in which the radiation from a sound source is completely unaffected by the presence of any reflecting boundaries.
Hertz (Hz)	Unit of frequency, equal to one cycle per second. The frequency of sound waves refers to the number of pressure fluctuations per second. Frequency is related to the pitch of a sound.
$L_{Aeq,T}$	The equivalent steady sound level in dB(A) containing the same acoustic energy as the actual fluctuating sound level over the given period, T. For example, daytime noise is generally measured over a 16 hour period, so T is 16 hours. $L_{Aeq,T}$ can be measured directly with an integrating sound level meter.
L_{A10}	The 'A'-weighted sound pressure level of the residual noise in decibels exceeded for 10 percent of a given time and is the $L_{A10,T}$. The L_{A10} is used to describe the levels of road traffic noise at a particular location.
L_{A50}	The 'A'-weighted sound pressure level of the residual noise in decibels exceeded for 50 percent of a given time and is the $L_{A50,T}$.
L_{A90}	The 'A'-weighted sound pressure level of the residual noise in decibels exceeded for 90 percent of a given time and is the $L_{A90,T}$. The L_{A90} is used to describe the background noise levels at a particular location.
L_{Amax}	The 'A'-weighted maximum sound pressure level measured over a measurement period.
R_w (or SRI)	The weighted sound reduction index as a single number laboratory measured rating used to describe the sound insulation of building elements.

Appendix 2 Schedule of Equipment

Appendix 2: Schedule of Equipment

Hawkins Noise Kit 1 - Equipment Set 3056:

Equipment Type	Manufacturer	Serial Number	Calibration Certification Number	Calibration Type	Date of Last Calibration Check	Date of Next Calibration Check
Nor-140 Type 1 Sound Level Meter	Norsonic	1403056	U42312	UKAS Calibration: 0789	2 nd November 2022	November 2024
Nor-1209 Pre-amplifier	Norsonic	12528	U42312	UKAS Calibration: 0789	2 nd November 2022	November 2024
Nor-1225 Microphone	Norsonic	98361	42311	UKAS Calibration: 0789	2 nd November 2022	November 2024
Nor-1255 Sound Calibrator	Norsonic	25262	U46043	UKAS Calibration: 0789	24 th November 2023	November 2024
Nor-1284 Dehumidifier	Norsonic	222	Not Applicable			
Nor- 1212 Weather Protection Kit	Norsonic	Not Applicable				
Nor1408A/10 Extension Cable	Norsonic/Lemo	Not Applicable				

Acoustic Impact Assessment:
Coldharbour Road, Gravesend
Simply UK • 16th August 2024 • H4223 – NV – v3

Laboratory Location

Campbell Associates Ltd
5b Chelmsford Road Industrial Estate
GREAT DUNMOW, Essex, GB-CM6 1HD
Phone 01371 871030



Certificate of Calibration and Conformance

Certificate number: **U42312**

Test Object: **Sound Level Meter, BS EN IEC 61672-1:2003 Class 1**

Producer: **Norsonic AS.**
Type: **140**
Serial number: **1403056**
Customer: **Hawkins Environmental**
Address: **The Square, Basing View,
Basingstoke, Hampshire, RG21 4EB**
Contact Person: **Nick Hawkins**
Order No: **TBC**

Introduction:

Calibration has been performed as set out in CA Technical Procedures which are based on the procedures for periodic verification of sound level meters as per the Test Object listed above. Results and conformance statement are overleaf and detailed results, where appropriate, are provided in the attached Measurement Report.

Tested:	Producer	Type	Serial No	Certificate No
Microphone	Norsonic	1225	98361	42311
Calibrator*	Norsonic	1255	125525262	U42310
Preamplifier	Norsonic	1209	12528	Included

* The calibrator was complete with any required coupler for the microphone specified.

Additional items that have also been submitted for verification:

Wind shield N/A
Attenuator N/A
Extension cable N/A

These items have been taken into account wherever appropriate.

Instruction Manual: Im140_1Ed8R0En Firmware Version: 2.1.670 The test object is a single channel instrument.

Conditions	Pressure kPa	Temperature °C	Humidity %RH
Reference conditions	101.325	23	50
Measurement conditions	100.82 ±0.08	23.40 ±0.2	47.98 ±0.2

Calibration Dates:

Received date:	24/10/2022	Reviewed date:	03/11/2022
Calibration date:	02/11/2022	Issued date:	03/11/2022

Technicians: (Electronic certificate)

Calibrated by: *Katie Brown*

Reviewed by: *Jenny Crawford*

This certificate is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to the SI system of units and/or to units of measurement realised at the National Physical Laboratory or other recognised national metrology institutes. This certificate may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

Doc ref: Slim-Cert-Master-V3-05

Certificate of Calibration and Conformance

Continuation of Certificate number: U42312

The statements of conformance and observation notes detailed in this certificate are made with reference to the following standards in respect of the calibration of the test object.

Manufactured: BS EN IEC 61672-1:2003
Periodic Tests: BS EN IEC 61672-3:2006
Pattern Evaluation: BS EN IEC 61672-2:2003

Conformance:

From markings on the sound level meter or by reference to the manufacturer's published literature it has been determined that the instrument submitted for verification was originally manufactured to the listed standard and similarly that the associated sound calibrator conforms to the BS EN IEC 60942 standard.

Measurement Summary:

Indication at the calibration check frequency - IEC61672-3 Ed.1 #9	Passed
Self-generated noise - IEC 61672-3 Ed.1 #10.2	Passed
Acoustical signal tests of a frequency weighting - IEC 61672-3 Ed.1 #11	Passed
Electrical signal tests of frequency weightings - IEC 61672-3 Ed.1 #12	Passed
Frequency weightings: A Network - IEC 61672-3 Ed.1 #12.3	Passed
Frequency weightings: C Network - IEC 61672-3 Ed.1 #12.3	Passed
Frequency weightings: Z Network - IEC 61672-3 Ed.1 #12.3	Passed
Frequency and time weightings at 1 kHz IEC 61672-3 Ed.1 #13	Passed
Level linearity on the reference level range - IEC 61672-3 Ed.1 #14	Passed
Toneburst response - IEC 61672-3 Ed.1 #16	Passed
Peak C sound level - IEC 61672-3 Ed.1 #17	Passed
Overload indication - IEC 61672-3 Ed.1 #18	Passed

Comments

Correct level with associated calibrator is 113.9dB(A). Actual measured microphone response has been used for the determination of the combined acoustic and electrical frequency response.

Statement of Conformance

The sound level meter submitted has successfully completed the periodic tests of the standard listed for the environmental conditions under which the tests were performed. As public evidence(1) was available, from an independent testing organisation responsible for approving the results of pattern evaluation tests performed in accordance with the manufacturer's standard to demonstrate that the model of sound level meter fully conformed to the requirements of the said standard, the sound level meter submitted for testing conforms to the relevant class of the said standard.

(1 - evidence is held on file at the calibration laboratory)

Observations

The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor $k = 2$, providing a coverage probability of approximately 95 %. The uncertainty evaluation has been carried out in accordance with UKAS requirements. Details of the uncertainty for each measurement are available from the Calibration Laboratory upon request. Details of the sources of corrections and their associated uncertainties that relate to this verification are contained within the test report accompanying this certificate.

Decision Rule

Basic Meter Function - The decision rules will be applied in accordance with the procedure as described in BS EN 61672-3:2006.

This certificate relates only to the items tested above.

** End of Certificate **

Laboratory Location

Campbell Associates Ltd
5b Chelmsford Road Industrial Estate
GREAT DUNMOW, Essex, GB-CM6 1HD
Phone 01371 871030

**Certificate of Calibration**

Certificate number: **42311**

Test Object: **Measurement Microphone**

Producer: **Norsonic AS.**
Type: **1225**
Serial number: **98361**
Customer: **Hawkins Environmental**
Address: **The Square, Basing View,
Basingstoke, Hampshire, RG21 4EB**
Contact Person: **Nick Hawkins**
Order No: **TBC**

Measurement Results	Sensitivity (dB re 1V/Pa)	Sensitivity (mV/Pa)	Capacitance (pF)
Measurement 1	-25.95	50.39	26.46
Measurement 2	-25.97	50.32	26.44
Measurement 3	-25.96	50.32	26.40
Result (Average):	-25.96	50.34	26.43
Expanded Uncertainty:	0.10		2.00
Degree of Freedom:	>100		>100
Coverage Factor:	2		2

The stated sensitivity is the pressure sensitivity at 250Hz, S₂₅₀, and is valid at reference conditions. The following correction factors have been applied during the measurement:

Pressure:uncertainty dB/kPa Temperature:-0.005 dB/°C Humidity:0 dB/%RH

Conditions	Pressure kPa	Temperature °C	Humidity %RH
Reference conditions	101.325	23	50
Measurement conditions	100.988 ± 0.042	22.9 ± 0.1	48.7 ± 0.8

The calibration test report shown on the next page gives details of the response at other frequencies relative to this 250 Hz reference sensitivity. Results ≥100 Hz are obtained using an electrostatic actuator as described in BS EN 61094-6 and those below 100 Hz are obtained in a reference pressure chamber. Detailed results are available from the calibration laboratory upon request.

The reported expanded uncertainty of measurements is based on a standard uncertainty multiplied by the coverage factor of k=2, providing a coverage probability of approximately 95%. Where the degrees of freedom are insufficient to maintain this confidence level, the coverage factor is increased to maintain this confidence level.

Calibration Dates:

Received date: 24/10/2022 Reviewed date: 03/11/2022
Calibration date: 02/11/2022 Issued date: 03/11/2022

Technicians: (Electronic certificate)

Calibrated by: *Katie Brown*
Reviewed by: *Jenny Crawford*

This certificate is issued in accordance with the CA Quality Management system. It provides traceability of measurement to recognized national standards, and to the units of measurement realized at the National Physical Laboratory or other recognized national standards laboratories. This certificate may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

Doc ref: Mic-Cert-Master-V3-04

Certificate of Calibration

Continuation of Certificate number: 42311

Reference Calibrator: WSC11 - Nor-1253.26672

Measurement Record: K:\C A\Calibration\Nor-1504\Nor-1017 MicCal\NOR1225_98361_M1.nmf

Preconditioning

The equipment was preconditioned for more than 12 hours at the specified calibration temperature and humidity.

Instruments and Program

A complete list of instruments, hardware and software that have been used for this calibration is available from the calibration laboratory

Traceability

The measured values for sound pressure, frequency, voltage, capacitance, temperature, humidity and ambient pressure are traceable to an accredited national physical laboratory.

Observations

The differences between the two results at 100 Hz are within normal limits bearing in mind the different test methods and are taken into account in arriving at the uncertainties of measurement.

Method of Calibration

The open circuit sensitivity of the microphone has been determined at 250 Hz against a reference laboratory standard measurement microphone by insert voltage techniques using a laboratory standard sound calibrator as a transfer standard. The electrostatic actuator frequency response was then obtained for frequencies above 100 Hz as described in BS EN IEC 61094-8. In addition, where requested the optional free field frequency response over the range 2 – 100 Hz has been obtained using a pressure chamber; in this case the reference frequency is 100 Hz. All of these results and their associated uncertainties are detailed in the table on page 3 of this certificate. See the observations field below for details of any discrepancies between the 100 Hz results obtained via the electrostatic actuator and pressure chamber.

The overall uncertainty at any frequency $\sigma_{\text{Combined},Fn}$ may be obtained by combining the uncertainty of the open circuit sensitivity σ_{S250} with the uncertainty of the actuator / or LF pressure response at any other frequency $\sigma_{\text{Act},Fn}$ where Fn is the uncertainty at the frequency of interest using the relationship:

$$\sigma_{\text{Combined},Fn} = 2\sqrt{(\sigma_{S250}^2 + \sigma_{\text{Act},Fn}^2)}$$

Appendix to this certificate

Where data is available from the microphone manufacturer to correct the actuator / pressure frequency response to obtain the random incidence and / or free field response it is shown in the appendix to this certificate. The uncertainty information relating to these corrections is the responsibility of the microphone manufacturer and when it is available the total uncertainty for the corrected frequency response at each point may then be obtained by including the correction uncertainty in the root-sum-square formula given above. These responses are outside the UKAS accredited scope, but are provided for information.

Observations

Certificate of Calibration

Page 2 of 4

Laboratory Location

Campbell Associates Ltd

5b Chelmsford Road Industrial Estate
GREAT DUNMOW, Essex, GB-CM6 1HD
Phone 01371 871030

**Certificate of Calibration and Conformance**Certificate number: **U46043**Test Object: **Sound Calibrator**

Producer: **Norsonic AS.**
Type: **1255**
Serial number: **125525262**
Customer: **Hawkins Environmental**
Address: **The Square, Basing View, Basingstoke,
Hampshire. RG21 4EB.**
Contact Person: **Nick Hawkins.**
Order No: **H8965**

Measurement Results	Level dB	Level Stability dB	Frequency Hz	Distortion %
Measurement 1	114.04	0.01	999.99	0.36
Measurement 2	114.04	0.02	999.99	0.36
Measurement 3	114.04	0.01	1000.00	0.38
Result (Average):	114.04	0.01	999.99	0.37
Expanded Uncertainty:	0.1	0.02	1	0.25
Degree of Freedom:	>100	>100	>100	>100
Coverage Factor:	2	2	2	2

The stated level is relative to 20µPa. The level is traceable to National Standards. The stated level is valid at reference conditions. The following correction factors have been applied during the measurement

Pres:0 dB/kPa Temp:0 dB/°C Humi:0 dB/%RH Load volume: 0.00015 dB/mm³

Conditions	Pressure kPa	Temperature °C	Humidity %RH
Reference conditions	101.325	23	50
Measurement conditions	101.328 ±0.042	20.9 ±0.1	40.3 ±1.4

The reported expanded uncertainty of measurements is based on a standard uncertainty multiplied by the coverage factor of k=2, providing a level of confidence of approximately 95%. Where the degrees of freedom are insufficient to maintain this confidence level, the coverage factor is increased to maintain this confidence level. The uncertainty has been determined in accordance with UKAS requirements.

Records: K:\C A\Calibration\Nor-1504\Nor-1018 CalCalCurrent Year\NOR1255_125525262_M1.nmf

Preconditioning

The equipment was preconditioned for more than 4 hours in the specified calibration environment.

Method

Calibration has been performed as set out in the current version of CA Technical procedure TP01

Calibration Dates:

Received date:	22/11/2023	Reviewed date:	24/11/2023
Calibration date:	24/11/2023	Issued date:	24/11/2023

Technicians: (Electronic certificate)

Calibrated by: *Michael Tichner*
Reviewed by: *Jenny Crawford*

This certificate is issued in accordance with the laboratory accreditation requirements of the United Kingdom Accreditation Service. It provides traceability of measurement to the SI system of units and/or to units of measurement realised at the National Physical Laboratory or other recognised national metrology institutes. This certificate may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

Doc ref: Calb-Cert-Master-V3-06

Certificate of Calibration and Conformance

Continuation of Certificate number: U46043

Reference Microphone: WSM8 (A) - GRAS-40AG.147852

Measurements

The calibrator has been tested as described in the following annexes to BS EN IEC60942:2003 Sound Calibrators; B3.4 for sound pressure level, B3.5 for frequency, B3.6 for total distortion and A4.4 for short term stability of the pressure level.

Instruments and Program

A complete list of instruments, hardware and software that have been used for this calibration is available from the calibration laboratory

Comments

Statement of Conformance and Calibration

As public evidence was available*, from a testing organisation responsible for approving the results of pattern evaluation tests, to demonstrate that the model of sound calibrator fully conformed to the requirements for pattern evaluation described in annex A of BS EN IEC 60942:2003, the sound calibrator tested is considered to conform to all the class 1 requirements of that BS EN IEC 60942:2003.

*This evidence is held on file at the calibration laboratory.

Notes:

The sound pressure level generated by the calibrator in its 1/2 inch configuration was measured five times and averaged by a WS2P working standard microphone for class 1 or 2 devices or a LS2P reference microphone for class 0 or LS devices as specified in the International Standard BS EN 61094-4. The results of three replications and the mean of the measurements obtained are given in the measurement results table of this certificate. The frequency and distortion were measured in a similar manner. The figures in BOLD are the final results; a small correction factor may need to be added to the sound pressure level quoted here if the device is used to calibrate a sound level meter that is fitted with a free field response microphone. See manufacturer's handbooks for full details of this and other corrections that may be applicable.

Observations:

Decision Rule:

The decision rules have been applied in accordance with the procedure as described in BS EN 60942:2003

This certificate relates only to the items tested above.

**** End of Certificate ****

Appendix 3 Summary of Sound Measurements

Appendix 3: Summary of Sound Measurements

Time	L _{Aeq}	L _{Amax}	L _{A10}	L _{A50}	L _{A90}
07:00	67.7	83.8	71.6	64.5	57.6
08:00	67.4	79.4	71.2	64.9	57.7
09:00	67.5	83.2	71.3	64.8	57.7
10:00	68.3	84.2	71.9	66.5	58.8
11:00	67.4	82.4	71.1	65.1	57.1
12:00	67.4	79.2	71.0	65.9	57.9
13:00	68.0	85.2	71.4	66.1	58.1
14:00	67.4	83.2	71.0	65.3	56.8
15:00	68.1	91.9	71.3	66.4	58.2
16:00	69.2	99.2	71.9	67.1	59.2
17:00	68.9	79.8	72.2	67.9	60.2
18:00	68.9	94.3	71.4	65.9	57.6
19:00	66.9	77.6	70.8	63.9	56.2
20:00	67.0	82.5	70.8	64.2	55.4
21:00	66.1	80.6	70.2	61.3	52.7
22:00	64.9	79.7	69.5	58.4	50.5
23:00	65.9	101.5	67.1	52.7	47.8
00:00	60.3	78.2	62.3	49.3	45.3
01:00	58.4	81.2	58.0	46.6	44.0
02:00	57.1	77.8	56.3	46.3	43.7
03:00	57.9	77.3	57.2	47.9	45.6
04:00	59.4	77.7	61.0	50.5	48.5
05:00	63.2	79.6	67.2	56.3	52.9
06:00	66.1	81.8	70.6	60.9	55.5
Day	67.7	99.2	71.2	64.9	57.0
Night	62.4	101.5	62.4	51.3	47.9

Appendix 4

Substation Data from Manufacturer

Appendix 4: Fan Data from Manufacturer


EcoDesign Tier 2 Trihal – Weights, dimensions, technology & acoustic attributes

Note: Table details IP00 core and coil type transformers – no enclosure

Rated power	kVA	500	630	800	1000	1250	1600	2000	2500	3150
Length (L)	mm	1410	1420	1500	1530	1660	1750	1800	1840	1980
Width (W)	mm	800	800	800	950	950	950	1230	1230	1270
Height (H)	mm	1450	1550	1680	1860	1780	1940	2130	2330	2560
Total weight	kg	1459	1652	2060	2368	2874	3460	3960	4700	6120
Technology										
PIR : Pre-Impregnated Resin on foil conductor	LV	PIR	PIR	PIR	PIR	PIR	PIR	PIR	PIR	PIR
VCR: glass-fibre insulated winding, encapsulated in Vacuum Cast Resin	HV	VCR	VCR	VCR	VCR	VCR	VCR	VCR	VCR	VCR
Noise level										
Sound power Lw(A)	dB(A)	60	61	63	64	66	67	69	70	73
Sound pressure at 1 m Lp(A)	dB(A)	47	48	50	50	52	53	55	55	58

Examples in table above refer to IP00 transformer only, with standard terminations and without an enclosure. If indoor enclosure is required (e.g. IP21 or IP31), please consult your Schneider Electric representative.

The dimensions and weights are approximate only (+/-200mm and +/-20%kg). Schneider Electric will only be held responsible for certified drawings that are issued after order.



Life is On | Schneider Electric 17