

PRODUCT TECHNICAL INFORMATION SHEET

PRODUCT NAME : JASMINE BLEND
REF. CODE : 166110
DESCRIPTION : RED MULTI
MANUFACTURE : SOFT MUD, MOULDED STOCK
APPEARANCE : SANDED STOCK
CONFIGURATION : FROGGED - MAX 20%
WORK SIZE * : 215 x 102 x 65

GUARANTEED PROPERTIES EN771-1: 2003

COMPRESSIVE STRENGTH : MIN. **12N/mm²**
WATER ABSORPTION : MAX. **17%**
DURABILITY DESIGNATION : **F2**
ACTIVE SOLUBLE SALTS : **S2**
SIZE TOLERANCE * (/ RANGE) : **T2- R1**
GROSS DENSITY (Tolerance) : **1600Kg/m³ (D1)**
NET DENSITY (Tolerance) : **1750Kg/m³ (D1)**
THERMAL CONDUCTIVITY ($\lambda_{10, dry}$) : P=90% **0.47W/m.K**
INITIAL RATE OF WATER ABS. : **6.0Kg/m².minute**
BOND STRENGTH (General Mortar) : **0.15N/mm² (fixed value)**
REACTION TO FIRE : Class **A1**
WATER VAPOUR PERMEABILITY (μ) : **5/10 (tabulated)**
PACK QUANTITY : **528 no**
TYPICAL PACK WEIGHT : **1316 Kg**