



LIGNUM
Timber Windows & Doors
Created by The Joinery Network

Box Sash Window

Traditional box sash windows are the enduring design of grand Georgian houses, Victorian villas and elegant Edwardian homes.

Lignum Sliding Sash Windows offer an authentic conservation replacement to retain the traditional features of a period property renovation.

The window provides excellent energy efficiency and security performance, making it an ideal choice for both refurbishment and new build projects.



PAS 24:2016
Security



1.3W/m²K
U-Value



Secured by Design
System



Document L
Compliant



Document M
Compliant



BS6375-1 2009
Weather Tightness



Double or Triple
Glazing

Specification

Frame Options	102 x 164mm Head & Jambs 68 x 164mm Cill 98mm, 141mm * 198mm Mullion 28mm Transom
Sash	56 x 57mm Top Rail & Stiles 90 x 57mm Bottom Rail 43 x 57mm Meeting Rails
Sash Profile	Ovolo or Lambs Tongue
Cill Projection	35mm Flush 60mm, 85mm or 110mm
Glazing	24mm Low E Sealed Unit (4mm/16mm/4mm) Obscure, Sound Control, Toughened and Laminated Options Available Argon Filled Cavity, Outer perimeter has Standard Warm Edge Spacer (Black) Optional White Security Bead Glazing System Additional glazing units include 12mm and 14mm options Curved glass and units with less than 14mm cavity will have Aluminium Spacer in place of Warm Edge Spacer
Trickle Vent	Concealed Trickle Vent Through Head 4600EA

Hardware/Fittings

Hardware	Sash catch, sash lifts, sash restrictors and barrel security lock 2 sash catches fitted if frame are PAS 24 security
Handles	Polished Chrome, Satin Chrome, Antique Brass, Oil Rubbed Bronze or Brass Finish
Trickle Vent	Can be fitted through head (Concealed)

Test Data

BS6375 Part 1	Air Permeability Class 3, Watertightness Class 8A to 450PA Resistance To Wind Load Class C5
Acoustic Rating	RW(C;Ctr) = 36 (-2,6) db (With Sound Control Glass)
Thermal Rating	U-Value 1.3W/m ² K
Security	PAS 24 and Secured by Design

The Joinery Network

