

CEDRAL



The World of Roofs

FIBRE CEMENT SLATES

PROTECT YOUR ROOF AND WHAT'S UNDER IT





WHY CHOOSE CEDRAL SLATES FOR YOUR ROOF?

Our British Heritage
An integral part of homes across the UK for over a century, Cedral slates have deep-rooted history and heritage.
Formerly under the brand name of Eternit we are the UK's most experienced company when it comes to fibre cement slates and are proud to have been putting roofs over heads for decades.
As part of the global building materials group Etex, our residential range of products now unites worldwide under the Cedral brand, offering you more choice, more services and more expertise to make your build as easy as possible.

CONTENTS



3 WHY CHOOSE CEDRAL SLATES FOR YOUR ROOF?



5 WHY CHOOSE FIBRE CEMENT?



6 RIVENDALE



8 BIRKDALE



10 THRUTONE SMOOTH



12 THRUTONE TEXTURED



14 CASE STUDIES



18 PROPERTIES & PERFORMANCE



20 SUPPORT & BACK-UP



22 SUSTAINABILITY & ENVIRONMENT



Beautiful, affordable, sustainable
We are committed to driving the industry forward by developing beautiful, affordable and environmentally sustainable building products. Everything we do is underpinned by a dedication to striking a balance between aesthetics and quality, along with eco-friendliness, as sustainability and energy efficiency become more prevalent than ever before.
With local advisors across all corners of the UK as well as a dedicated internal customer service and technical support department, the Cedral team are on hand to guide you through every stage of your project.

WHY CHOOSE FIBRE CEMENT?

Fibre cement is a durable mineral material, lightweight and weather resistant. Composed of cement, cellulose, sand, synthetic fibres and water; it is incredibly strong, versatile and has many advantages.



Durable

Fibre cement is tough enough to withstand the most volatile weather conditions (frost, heavy rain, intense heat, light etc).



Fire resistant

Fibre cement has excellent fire behaviour (fire class A2-s1, d0 according to EN 13501-1:2018).



Sustainable

While fibre cement has been around for decades, innovations in technology ensure it contributes to eco-construction and respects the environment. A light-weight material, it considerably reduces the carbon footprint of any build.



Kerb appeal

Our slates come in a range of beautiful colours, textures and shapes and can be installed in many different ways, meaning you can choose to fit in or stand out.

YOUR HOME EXPRESSES WHO YOU ARE & WHAT YOU LIKE

Your personality is reflected in your interior but also in the exterior of your home. Your roof must also stand the test of time. Cedral fibre cement slates are an ideal material offering both beauty and performance. Our slates are the strongest on the market and offer maximum design scope, so whatever your roofing project, Cedral has got you covered.



THRUTONE TEXTURED FIBRE CEMENT SLATES

Cedral Thrutone Textured slates offer the same strength and durability as our flagship smooth slate, but have a subtle, textured finish which will enhance any roof and home.



Technical data	
Size of slate	600mm x 300mm
Minimum pitch*	
Moderate exposure	22.5° (100mm lap) 20° (110mm lap)
Severe exposure	25° (100mm lap) 22.5° (110mm lap)
Maximum pitch	90°
Typical laps	100, 110mm
Maximum gauge	245-250mm
Slate thickness	4mm
Covering capacity (net)	13.4 slates/m² at 100mm lap 13.6 slates/m² at 110mm lap
Weight of slating (approx.)	20.4 kg/m² (0.20 kN/m²) at 100mm lap 20.9 kg/m² (0.20 kN/m²) at 110mm lap
Battens required (net)	4.00 lin.m/m² at 100mm lap 4.08 lin.m/m² at 110mm lap
Batten size recommended (fixed to BS 5534)	38 x 25mm for rafters/supports not exceeding 450mm centres 50 x 25mm for rafters/supports not exceeding 600mm centres
Fixings	Slate nails (30 x 2.65mm) Copper disc rivets (19mm dia. x 2mm stem)
Fittings screws	14 gauge self sealing
Authority	BS EN 492
Cedral fibre cement slates meet the strength requirement of BS EN 492, achieving an average bending movement greater than 50 NM/M (Class B). Cedral Fibre Cement Slates have an average density of 1970kg/m³ (minimum of 1750kg/m³) when tested to BS EN492 and a nominal thickness of 4mm. * The minimum recommended pitch and lap may be influenced by special circumstances, please contact the Technical Advisory Team. † Made to order	

Sustainability	
Green guide rating	A+ (Element ref: 812410008)
BES 6001	Very good – can achieve 3 credits
Credit uplift available with EPD	
Embodied carbon	Low carbon footprint of 13 CO ₂ e/m²

The printing process restricts the exact representation of colours. For true colour reference, please request product samples.



✓ Detailed surface

✓ Square edges

✓ Resembles natural slate